

Synergy™ - cooker control units and fused connection units - Authentic



8 332 29

8 334 37

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

Pack	Cat.Nos	Cooker control units - 250 V~
		Conform to BS 4177: 1992 For flush-mounting, back box to be min. 47 mm deep Nominal plate dimensions: 86 x 146 mm
		45 A DP switch + 13 A DP switched socket outlet with blue LED power indicator
1	8 330 29	● Brushed stainless steel
1	8 332 29	● Polished stainless steel
1	8 334 29	● Glossy gold
		Fused connection units 13 A - 250 V~
		Conform to BS 1363: Part. 4 Front cable outlet with cord grip Fuse supplied Locked captive fuse carrier (padlockable) For flush-mounting, back box to be min. 25 mm deep
		Unswitched with cord outlet
		Nominal plate dimensions: 86 x 86 mm
1	8 330 32	● Brushed stainless steel
1	8 332 32	● Polished stainless steel
1	8 334 32	● Glossy gold
		Unswitched without cord outlet
		Nominal plate dimensions: 86 x 86 mm
1	8 330 30	● Brushed stainless steel
1	8 332 30	● Polished stainless steel
1	8 334 30	● Glossy gold
		Unswitched with blue LED power indicator
		Nominal plate dimensions: 86 x 86 mm
1	8 330 31	● Brushed stainless steel
1	8 332 31	● Polished stainless steel
1	8 334 31	● Glossy gold
		Unswitched with blue LED power indicator + cord outlet
		Nominal plate dimensions: 86 x 86 mm
1	8 330 33	● Brushed stainless steel
1	8 332 33	● Polished stainless steel
1	8 334 33	● Glossy gold
		DP switched without cord outlet
		Nominal plate dimensions: 86 x 146 mm
1	8 330 34	● Brushed stainless steel
1	8 332 34	● Polished stainless steel
1	8 334 34	● Glossy gold
		DP switched with blue LED power indicator
		Nominal plate dimensions: 86 x 146 mm
1	8 330 35	● Brushed stainless steel
1	8 332 35	● Polished stainless steel
1	8 334 35	● Glossy gold
		DP switched with blue LED power indicator + cord outlet
		Nominal plate dimensions: 86 x 146 mm
1	8 330 37	● Brushed stainless steel
1	8 332 37	● Polished stainless steel
1	8 334 37	● Glossy gold

Synergy™ - shaver sockets, cable outlets, blanking plates and cord outlets - Authentic



8 332 90

8 330 19

8 334 95

Slim front plates:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

Pack	Cat.Nos	Shaver sockets
		Conform to BS EN 61558-2-5 Suitable for use with European, British and Australian 2 pin plugs Rating: 20 VA IP 24 Screwless live and neutral terminals For flush-mounting, back box to be min. 45 mm deep Nominal plate dimensions: 146 x 86 mm
		230/120 V~ - 50/60 Hz
1	8 330 90	● Brushed stainless steel
1	8 332 90	● Polished stainless steel
1	8 334 90	● Glossy gold
		Cable outlets
		Conform to BS 5733 Fitted clamp and outlet membrane With terminal block Nominal plate dimensions: 86 x 86 mm
		20 A - 250 V~
1	8 330 19	● Brushed stainless steel
1	8 332 19	● Polished stainless steel
1	8 334 19	● Glossy gold
		45 A - 250 V~
1	8 330 26	● Brushed stainless steel
1	8 332 26	● Polished stainless steel
1	8 334 26	● Glossy gold
		Blanking plates
		1 gang
		Nominal plate dimensions: 86 x 86 mm
1	8 330 95	● Brushed stainless steel
1	8 332 95	● Polished stainless steel
1	8 334 95	● Glossy gold
		2 gang
		Nominal plate dimensions: 86 x 146 mm
1	8 330 96	● Brushed stainless steel
1	8 332 96	● Polished stainless steel
1	8 334 96	● Glossy gold
		Cord outlets
		1 gang
		Nominal plate dimensions: 86 x 86 mm
1	8 330 52	● Brushed stainless steel
1	8 332 52	● Polished stainless steel
1	8 334 52	● Glossy gold