



8 332 97



8 334 89



8 330 69



8 332 59



8 330 44

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	RCD sockets 13 A - 250 V~	Pack	Cat.Nos	Socket outlets 15 A - 127 V~
		<p>Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep</p> <p>ELO - DP 30 mA Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools</p> <p>ELR - DP 30 mA Trips in the event of a power failure Ideal for applications where it is desirable to automatically re-activate equipment after a power failure. E.g. fridge, freezer, unmanned areas</p>			<p>For flush-mounting, back box to be min. 35 mm deep</p> <p>1 gang Nominal plate dimensions: 86 x 86 mm</p> <p>2 gang Nominal plate dimensions: 86 x 146 mm</p>
		<p>AVAILABLE JULY 2016</p> <p>1 8 330 85 ● Brushed stainless steel 1 8 332 85 ● Polished stainless steel 1 8 334 85 ● Glossy gold</p> <p>2 gang - Nominal plate dimensions: 86 x 146 mm 1 8 330 97 ● Brushed stainless steel 1 8 332 97 ● Polished stainless steel 1 8 334 97 ● Glossy gold</p> <p>1 gang - Nominal plate dimensions: 86 x 86 mm 1 8 330 86 ● Brushed stainless steel 1 8 332 86 ● Polished stainless steel 1 8 334 86 ● Glossy gold</p> <p>2 gang - Nominal plate dimensions: 86 x 146 mm 1 8 330 98 ● Brushed stainless steel 1 8 332 98 ● Polished stainless steel 1 8 334 98 ● Glossy gold</p>			<p>1 8 330 99 ● Brushed stainless steel 1 8 334 99 ● Polished stainless steel 1 8 333 99 ● Glossy gold</p> <p>1 8 332 99 ● Brushed stainless steel 1 8 331 99 ● Polished stainless steel 1 8 335 99 ● Glossy gold</p>
		<p>AVAILABLE JULY 2016</p> <p>1 8 330 88 ● Brushed stainless steel 1 8 332 88 ● Polished stainless steel 1 8 334 88 ● Glossy gold</p> <p>1 gang switched - single pole 1 8 330 89 ● Brushed stainless steel 1 8 332 89 ● Polished stainless steel 1 8 334 89 ● Glossy gold</p>			<p>Socket outlets 5 A - 250 V~</p> <p>Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 25 mm deep</p> <p>1 gang unswitched Nominal plate dimensions: 86 x 86 mm</p> <p>1 8 330 68 ● Brushed stainless steel 1 8 332 68 ● Polished stainless steel 1 8 334 68 ● Glossy gold</p> <p>1 gang switched - single pole Nominal plate dimensions: 86 x 146 mm</p> <p>1 8 330 69 ● Brushed stainless steel 1 8 332 69 ● Polished stainless steel 1 8 334 69 ● Glossy gold</p>
		<p>Socket outlets 15 A - 250 V~</p> <p>Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm</p> <p>1 gang unswitched 1 8 330 59 ● Brushed stainless steel 1 8 332 59 ● Polished stainless steel 1 8 334 59 ● Glossy gold</p>			<p>Socket outlets 2 A - 250 V~</p> <p>Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm</p> <p>1 gang unswitched 1 8 330 59 ● Brushed stainless steel 1 8 332 59 ● Polished stainless steel 1 8 334 59 ● Glossy gold</p>
		<p>Double USB sockets</p> <p>For flush-mounting, back box to be min. 40 mm deep Input voltage: 110 V/ 230 V Comply with IEC 62684 5 V (output) - 2400 mA Wiring with 1.5 Sq.mm and 2.5 Sq.mm (only live and neutral)</p> <p>1 8 330 44 ● Brushed stainless steel 1 8 332 44 ● Polished stainless steel 1 8 334 44 ● Glossy gold</p>			