

CAT. N° 0 792 07



UNIVERSAL DIMMER MOSAIC - WITHOUT NEUTRAL - ALU - 2 MODULES

Pack (number of units)	1
Volume (dm ³)	0,547
Weight (g)	100,00

Product characteristics

Dimmer switches 110-230 V~ 50 Hz

- Can be remotely controlled via non-illuminated pushbuttons, with each pushbutton able to perform the dimming function
- When switched on, lighten at the level set before last switched off
- For installation in flush-mounting box depth 40 mm min

Universal dimmer without neutral, 2-wire

- For all types of lamps:
 - dimmable LEDs: 5 W to 75 W (10 lamps max.)
 - dimmable compact fluorescent lamps: 5 W to 75 W (10 lamps max.)
 - halogen with ferromagnetic or electronic transformer: 3 VA to 400 VA
 - fluorescent tube - ballast: 3 VA to 200 VA
 - halogen and incandescent 230 V: 3 W to 400 W
- When switched on, gradually (2 seconds) lights up at the level set before last switch-off
- Functioning:
 - dimming mode
 - pre-set level mode (0%, 33%, 66%, 100%)
 - nightlight mode: dimming down of the lamp for
 - 1 hour
 - 2 modules
 - Alu

General characteristics

Mosaic™ Programme mechanisms - dimming control

Documentation

Catalogue pages & additional information

- [Description page \(p.881\)](#)
- [Technical page \(p.882\)](#)

Installation & technical data

- [F01602EN-06](#)

Installation instructions & related documents

- [LE05368AE](#)

Agreements & certificates of conformity

- [NF-NF012_1945](#)
- [OC / CB-630164B/A1](#)