

Product sheet



MALLIA SENSES LEGRAND

Mallia Senses 3 gang 2 way Illuminated switch 16AX

REF. 281015BB | EAN. 3414972080637

No price to display

> [Visit e-catalogue](#)

Product charateristics

- 16AX, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Brushed black finish

Recommendations / Restrictions

- Recommended inside use only

The product's benefits

Installation

- Quick and Easy plate-rocker clipping system

Usage

- Practical 3-point lighting control on a single plate

Advantages

- Definite motion for a soft touch and sound
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

Technical characteristics

Wiring system	Intermediate switch
Method of operation	Rocker lever
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	3
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic

Switching current for fluorescent lamps	16 AX
Feedback-signal contact	No
Connection type	Screwed terminal
Heating switch	No
Washing machine switch	No
Device width	86 mm
Device height	86 mm
Device depth	36.8 mm
Built-in depth	24.9 mm

Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Metallic
Surface finishing	Matt
Colour	Black
Colour of switch operator	Black
Illumination	Optional
Function lighting	Control and orientation
Type of lighting	LED exchangeable
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	16 A





Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Frequency	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Terminals capacity	1-4 mm ²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm ²

Documentation

TECHNICAL DOCUMENTATION

 [F03220EN-01.pdf](#) | PDF (0.51Mo)

Agreements & Certificates

-  [OC / CB-CN52792](#) | (0.9Mo)
-  [OC / CB-CN52792-M1](#) | (1.4Mo)
-  [OC / CB-CN52792-M3](#) | (1.54Mo)
-  [OC / CB-CN52792-M2](#) | (1.2Mo)