


Rigid Connectors

Compression Type - Steel



Features

- Concrete tight when taped
- Threadless

Applications

- Used to join unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Malleable iron


Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
R-CCN050	½"	20	200	13	1.50	1.50
R-CCN075	¾"	10	100	20	1.50	1.63
R-CCN100	1"	5	50	36	1.687	2.00
R-CCN125	1-¼"	5	50	64	2.00	2.38
R-CCN150	1-½"	—	12	92	2.0625	2.63
R-CCN200	2"	—	12	117	2.25	3.31
R-CCN250	2-½"	—	5	14	3.00	3.75
R-CCN300	3"	—	3	13	3.125	4.25
R-CCN350	3-½"	—	2	13	3.187	4.75
R-CCN400	4"	—	2	13	3.437	5.312

Rigid Couplings

Compression Type - Steel



Features

- Compression type
- Concrete tight
- Threadless

Applications

- Used to join two lengths unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Malleable iron

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)	
					A	B
R-CCP050	½"	10	100	16	1.81	1.50
R-CCP075	¾"	10	100	24	1.87	1.62
R-CCP100	1"	5	50	48	2.18	2.00
R-CCP125	1-¼"	5	50	86	2.62	2.37
R-CCP150	1-½"	—	12	125	2.68	2.62
R-CCP200	2"	—	5	160	3.00	3.31
R-CCP250	2-½"	—	5	260	5.75	3.93
R-CCP300	3"	—	3	300	5.72	4.66
R-CCP350	3-½"	—	2	350	6.00	5.20
R-CCP400	4"	—	2	400	6.81	5.75