

# Rigid/intermediate grade conduit fittings

## Conduit clamps, straps, hangers

### CLAMPS – MALLEABLE IRON

#### Applications:

- To support rigid conduit and IMC to mounting surface

#### Options:

- Description** **Suffix**
- Hot dip galvanized ..... **HDG**

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
510	1/2"	100	6
511	3/4"	50	8
512	1"	50	13
513	1 1/4"	25	20
514	1 1/2"	20	30
515	2"	10	64
516 <sup>ⓐ</sup>	2 1/2"	5	104
517 <sup>ⓐ</sup>	3"	2	120
518 <sup>ⓐ</sup>	3 1/2"	2	150
519 <sup>ⓐ</sup>	4"	2	220
520 <sup>ⓐ</sup>	5"	1	380
521 <sup>ⓐ</sup>	6"	1	690

<sup>ⓐ</sup>Also for use with thin wall (EMT) conduit.  
<sup>ⓐ</sup>Not UL Listed.

### CLAMPBACKS/SPACERS – MALLEABLE IRON

#### Applications:

- To provide space between conduit and mounting surface

#### Standard materials:

- Stamped steel – 1/2" - 1 1/2"
- Malleable iron – 2" - 6"

#### Options:

- Description** **Suffix**
- Hot dip galvanized ..... **HDG**

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1 <sup>ⓐ</sup>	1/2"	25	8
CB2 <sup>ⓐ</sup>	3/4"	25	10
CB3 <sup>ⓐ</sup>	1"	25	12
CB4 <sup>ⓐ</sup>	1 1/4"	25	21
CB5 <sup>ⓐ</sup>	1 1/2"	25	42
CB6	2"	10	40
CB7	2 1/2"	10	49
CB8	3"	10	62
CB9	3 1/2"	10	91
CB10	4"	10	110
CB11 <sup>ⓐ</sup>	5"	5	135
CB12 <sup>ⓐ</sup>	6"	5	225

<sup>ⓐ</sup>Stamped steel.  
<sup>ⓐ</sup>Not UL Listed.

### STRAPS – STEEL GALVANIZED

#### Applications:

- Used to secure rigid conduit or IMC to mounting surface

#### Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
496 2	3/8"	250	2
496 3	1/2"	150	2
496 4	3/4"	100	3
496 5	1"	50	7
496 6	1 1/4"	50	8
496 7	1 1/2"	50	10
496 8	2"	25	15
496 9	2 1/2"	25	19
496 10	3"	25	23
496 11	3 1/2"	25	93
496 12	4"	10	108

### CLAMPS – STEEL

#### Applications:

- To support rigid conduit and IMC to mounting surface

#### Heavy gauge



Cat. #	Size	Unit qty.	Wt. lbs. per 100
410	1/2"	100	5
411	3/4"	50	6
412	1"	50	11
413	1 1/4"	50	13
414	1 1/2"	25	20
415	2"	25	22
206	2 1/2"	25	64
207	3"	25	71
208	3 1/2"	10	120
209	4"	10	130

### CLAMPS "SNAP-ON – STEEL

#### Applications:

- To support rigid conduit and IMC to mounting surface

#### Light gauge



Cat. #	Size	Size of strap inside	Unit qty.	Wt. lbs. per 100
567	3/8"	.675	200	2

Rigid fittings