

Rigid/intermediate grade conduit fittings

Set screw type fittings – malleable, steel, zinc die cast

SET SCREW TYPE FITTINGS – MALLEABLE, STEEL, ZINC DIE CAST

Standard materials:

- Malleable – 1/2" - 2", 5", 6"
- Steel – 2 1/2" - 4"
- Zinc die cast – 2 1/2" - 4"

Straight connectors – insulated

UL File No. E-19189



150S



1456



Cat. # Malleable/steel	Cat. # zinc die cast	Size	Unit qty.	Wt. lbs. per 100
150S		1/2"	50	16
151		3/4"	25	27
152		1"	5	40
153		1 1/4"	10	50
154		1 1/2"	5	76
155 ^A		2"	2	110
1456 ^A	1456DC ^A	2 1/2"	2	210 ^F
1457 ^A	1457DC ^A	3"	1	282 ^F
1458 ^A	1458DC ^A	3 1/2"	1	380 ^F
1459 ^A	1459DC ^A	4"	1	400 ^F

^A Two tightening screws.

^F Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 1456-1459 and 1456DC-1459DC are UL and cUL Listed for EMT, rigid and IMC conduit.

Couplings

UL File No. E-19189



160



466



Cat. # Malleable/Steel	Cat. # Zinc Die Cast	Size	Unit qty.	Wt. lbs. per 100
160		1/2"	25	27
161		3/4"	20	40
162		1"	5	52
163		1 1/4"	10	70
164		1 1/2"	5	104
165 ^B		2"	2	160
466 ^B	466DC ^B	2 1/2"	2	300 ^F
467 ^B	467DC ^B	3"	1	400 ^F
468 ^B	468DC ^B	3 1/2"	1	500 ^F
469 ^B	469DC ^B	4"	1	600 ^F
170C ^B		5"	1	1500
171C ^B		6"	1	1800

^B Four tightening screws.

^F Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 466-469 and 466DC-469DC are UL and cUL Listed for EMT, rigid and IMC conduit.

Straight connectors – non-insulated

UL File No. E-19189



150P



456



Cat. # Malleable/Steel	Cat. # Zinc Die Cast	Size	Unit qty.	Wt. lbs. per 100
150P		1/2"	50	16
151P		3/4"	25	26
152P		1"	5	40
153P		1 1/4"	10	50
154P		1 1/2"	5	76
155P		2"	2	110
456 ^A	456DC ^A	2 1/2"	2	210 ^F
457 ^A	457DC ^A	3"	1	281 ^F
458 ^A	458DC ^A	3 1/2"	1	380 ^F
459 ^A	459DC ^A	4"	1	400 ^F
160P ^A		5"	1	850
161P ^A		6"	1	1100

^A Two tightening screws.

^F Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 456-459 and 456DC-459DC are UL and cUL Listed for EMT, rigid and IMC conduit.