Condulet® Conduit Outlet Boxes With Covers

GUA Series

Cl. I, Div. 1 & 2, Groups C, D Cl. II, Div. 1, Groups E, F, G Cl. II, Div. 2, Groups F, G Cl. III NEMA 3, 4, 7CD, 9EFG Explosionproof
Dust-Ignitionproof
Raintight
Wet Locations

유

Applications:

GUA series conduit outlet boxes are installed within hazardous area conduit systems to:

- Protect conductors in threaded rigid conduit
- · Act as pull and splice boxes
- · Connect lengths of conduit
- Change conduit direction
- Provide access to conductors for maintenance and future system changes
- Act as mounting outlets for fixtures (with appropriate covers)
- Act as sealing fittings (with appropriate covers)

Features:

GUA conduit boxes have:

- Neoprene "O" ring standard to meet NEMA 4 requirements
- Cast ears on cover to permit easy removal and tightening
- Four standard mounting pads except for boxes with bottom hubs
- Threaded cover openings
- Ten different hub arrangements
- Taper threaded hubs to provide grounding continuity
- Smooth integral hub bushing protects conductor insulation when pulling
- Surface covers furnished with boxes
- Sealing covers, dome covers, and fixture hanger covers are available
- Cover threads are 12 pitch

Certifications and Compliances:

• NEC/CEC:

Class I, Division 1 & 2, Groups C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III

- UL Standard: 1203
- ANSI Standard: C33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4

Standard Materials:

- Bodies Feraloy iron alloy
- Covers Copper-free aluminum

Standard Finishes:

- Feraloy iron alloy electrogalvanized and aluminum acrylic paint
- Aluminum natural

Size Ranges:

- Hub 1/2" to 2"
- Cover opening 2" to 5" dia.

Options:

Description	Suffix
Bodies - copper-free aluminum	SA†*
Covers - Feraloy iron alloy -	
electrogalvanized and aluminum	
acrylic paint	WOD
GUA Form 6 (with 3" cover opening)	
are available with optional cover	
with viewing window.	VW
Corro-free epoxy powder coat	S752
To order box less cover add "0" to e	nd of
catalog number ie.GUAT260.	

When assembled with sealing type cover, GUA series outlet boxes provide adequate sealing for 40% fill in hazardous areas – Class I, Groups C, D; Class II, Groups E, F, G; and Class III. Seals can be made in either horizontal or vertical positions. Use *Chico*® "A" sealing compound or *Chico*® SpeedSeal only. Conductor splices or connections must not be made in enclosures where sealing compound is to be used per NEC.

GUA



Hub Size	Opening Dia.	Cat. #
1/2	2	GUA14
3/4	2	GUA24
1/2	3	GUA16
3/4	3	GUA26*
1	3	GUA36
11/4	35/8	GUA47
11/2	5	GUA59

GUAC



Hub Size	Cover Opening Dia.	Cat. #
1/2	2	GUAC14†
3/4	2	GUAC24†
1/2	3	GUAC16*
3/4	3	GUAC26*
1	3	GUAC36*
11/4	35/8	GUAC47†
11/4	5	GUAC49
11/2	5	GUAC59†
2	5	GUAC69†

†Available in copper-free aluminum, add suffix -SA. *Available in copper-free aluminum, add suffix -SA. GUA outlet boxes marked with * when ordered with suffix -SA are listed for Class I, Division 1 & 2, Groups B, C and D, Class II, Division 1, Groups E, F, G and Class III. Covers have 16 pitch threads. Replacement cover is a GUA06-GB.

GUAB

Cover




Hub Size	Opening Dia.	Cat. #
1/2	2	GUAB14†
3/4	2	GUAB24
1/2	3	GUAB16*
3/4	3	GUAB26*
1	3	GUAB36*
11/4	35/8	GUAB47†
11/2	5	GUAB59†
2	5	GUAB69†

GUAD



Hub	Cover Opening	
Size	Dia.	Cat. #
1/2	2	GUAD14†
3/4	2	GUAD24
1/2	3	GUAD16
3/4	3	GUAD26†
1	3	GUAD36†
11/4	5	GUAD49

Dimensions In Inches:



GUA, GUAD, GUAM, GUAW, GUAX

Cat. #	а	b	С	d	
14	21/2	1 13/ ₁₆	13/4	5/8	_
24	21/2	2	2	3/4	
16	31/2	2	17/8	5/8	
26	31/2	2	17/8	3/4	
36	31/2	25/16	23/16	7/8	
37	$4^{1}/_{4}$	25/16	23/8	7/8	
47	$4^{1}/_{4}$	211/16	23/4	13/32	
49	53/4	313/16	33/4	13/32	
59	53/4	313/16	33/4	19/32	
69	5 ³ / ₄	41/16	4	19/16	

Length of Hub Hub Size	Dimension "e" Length
1/2 - 3/4	⁷ / ₈
1 - 11/4	1
11/2 - 2	1 1/ ₁₆

Crouse-Hinds

Condulet® Conduit Outlet Boxes With Covers

GUA Series

Cl. I, Div. 1 & 2, Groups C, D Cl. II, Div. 1, Groups E, F, G Cl. II, Div. 2, Groups F, G CI. III NEMA 3, 4, 7CD, 9EFG

Explosionproof Dust-Ignitionproof Raintight Wet Locations

GUAL



Hub Size	Cover Opening Dia.	Cat. #
1/2	2	GUAL14†
3/4	2	GUAL24†
1/2	3	GUAL16*
3/4	3	GUAL26*†
1	3	GUAL36*
1 1/4	35/8	GUAL47†
1 1/4	5	GUAL49†
1 1/2	5	GUAL59†
2	5	GUAL69†

GUAN



Cover Opening Dia.	Cat. #
2	GUAN14
2	GUAN24
3	GUAN16
3	GUAN26
3	GUAN36†
35/8	GUAN47
5	GUAN59†
5	GUAN69
	Opening Dia. 2 2 3 3 3 3 5 5

GUAT



Hub Size	Cover Opening Dia.	Cat. #
1/2	2	GUAT14†
3/4	2	GUAT24†
1/2	3	GUAT16*
3/4	3	GUAT26*
1	3	GUAT36*
1	35/8	GUAT37
1 1/4	35/8	GUAT47†
1 1/4	5	GUAT49†
1 1/2	5	GUAT59†
2	5	GUAT69†

GUAX



Hub Size	Cover Opening Dia.	Cat. #
1/2	2	GUAX14†
3/4	2	GUAX24†
1/2	3	GUAX16*
3/4	3	GUAX26*
1	3	GUAX36*
1	35/8	GUAX37†
1 1/4	35/8	GUAX47†
1 1/4	5	GUAX49
1 1/2	5	GUAX59†
2	5	GUAX69†

GUAM



Cover Opening Dia.	Cat. #
2	GUAM14†
2	GUAM24
3	GUAM16
3	GUAM26
3	GUAM36
35/8	GUAM47
5	GUAM69
	Opening Dia. 2 2 3 3 3 3 55/8

GUAW



Hub Size	Cover Opening Dia.	Cat. #
1/2	2	GUAW14†
3/4	2	GUAW24†
1/2	3	GUAW16
3/4	3	GUAW26*†

Dimensions GUAC, GUAT

Cat. #	а	b	С	d
14	21/2	21/4	23/16	5/8
24	21/2	2	2	3/4
16	31/2	2	17/8	5/8
26	31/2	2	17/8	3/4
36	31/2	25/16	23/16	7/8
37	41/4	25/16	23/8	7/8
47	41/4	211/16	23/4	13/32
49	53/4	313/16	33/4	15/32
59	53/4	313/16	33/4	19/32
69	53/4	41/16	4	19/16

GUAN Cat. #	а	b	С
14	21/2	21/8	21/
24	21/2	25/16	21/
16	31/2	2	17/
	011	_	4 7 1

14	21/2	2 1/8	2 1/16	%
24	21/2	25/16	21/4	3/4
16	31/2	2	17/8	3/4
26	31/2	2	17/8	3/4
36	31/2	25/16	2 ³ / ₈	7/8
47	41/4	211/16	23/4	13/32
59	53/4	41/16	4	19/32
69	53/4	41/16	4	19/16

GUAB, GUAL

	_		
а	b	С	d
21/2	21/4	23/16	5/8
21/2	21/2	27/16	3/4
31/2	2	17/8	5/8
31/2	2	17/8	3/4
31/2	25/16	23/16	7/8
$4^{1}/_{4}$	211/16	23/4	13/32
$5^{3}/_{4}$	313/16	33/4	15/32
$5^{3}/_{4}$	313/16	33/4	19/32
53/4	$4^{1}/_{16}$	4	19/16
	2 ¹ / ₂ 2 ¹ / ₂ 3 ¹ / ₂ 3 ¹ / ₂ 3 ¹ / ₂ 4 ¹ / ₄ 5 ³ / ₄	2½ 2½ 2½ 2½ 3½ 2½ 3½ 2 3½ 2 3½ 2 1½ 2 ⁵ / ₁₆ 4¼ 2 ¹¹ / ₁₆ 5¾ 3 ¹³ / ₁₆ 5¾ 3 ¹³ / ₁₆	2½ 2½ 2½ 23/4 23/16 2½ 2½ 2½ 21/6 3½ 2 17/8 3½ 2 17/8 3½ 25/16 23/4 4¼ 211/16 23/4 53/4 333/16 33/4 53/4 333/16 33/4

†Available in copper-free aluminum, add suffix -SA.
*Available in copper-free aluminum, add suffix -SA. GUA outlet boxes marked with * when ordered with suffix -SA are listed for Class I, Division 1 & 2, Groups B, C and D, Class II, Division 1, Groups E, F, G and Class III. Covers have 16 pitch threads. Replacement cover is a GUA06-GB.