

# Thin wall conduit fittings (for EMT conduit)

Straps, clamps, clampbacks/spacers

## CLAMPBACKS/SPACERS – MALLEABLE IRON

### Applications:

- Provides space between conduit and mounting surface

### Standard materials:

- Stamped steel – 1/2" to 1 1/2"
- Malleable iron – 2" to 6"

### Standard finish:

- Zinc plated

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1 <sup>Ⓧ</sup>	1/2"	25	8
CB2 <sup>Ⓧ</sup>	3/4"	25	10
CB3 <sup>Ⓧ</sup>	1"	25	12
CB4 <sup>Ⓧ</sup>	1 1/4"	25	21
CB5 <sup>Ⓧ</sup>	1 1/2"	25	42
CB6	2"	10	40
CB7	2 1/2"	10	49
CB8	3"	10	62
CB9	3 1/2"	10	91
CB10	4"	10	110
CB11 <sup>Ⓧ</sup>	5"	5	135
CB12 <sup>Ⓧ</sup>	6"	5	225

<sup>Ⓧ</sup> Stamped steel.

<sup>Ⓧ</sup> Not UL Listed.

## STRAPS – STEEL GALVANIZED

### Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
497 1	1/2"	250	2
497 2	3/4"	150	3
497 3	1"	100	5
497 4	1 1/4"	50	8
497 5	1 1/2"	50	13
497 6	2"	25	14
496 9	2 1/2"	25	19
496 10	3"	25	23
496 11	3 1/2"	25	93
496 12	4"	10	108

## CLAMPS – MALLEABLE IRON

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
516 <sup>Ⓧ</sup>	2 1/2"	5	104
517 <sup>Ⓧ</sup>	3"	2	120
518 <sup>Ⓧ</sup>	3 1/2"	2	150
519 <sup>Ⓧ</sup>	4"	2	220

<sup>Ⓧ</sup> Also for use with rigid/IMC conduit.

## CLAMPS – STEEL

### Applications:

- To support EMT conduit to mounting surface

### Heavy gauge

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
200	1/2"	100	5
201	3/4"	100	6
202	1"	100	6
203	1 1/4"	50	13
204	1 1/2"	25	17
205	2"	25	20
206 <sup>Ⓧ</sup>	2 1/2"	25	64
207 <sup>Ⓧ</sup>	3"	25	71
208 <sup>Ⓧ</sup>	3 1/2"	10	120
209 <sup>Ⓧ</sup>	4"	10	130

<sup>Ⓧ</sup> Not UL Listed.