

# Rigid/intermediate grade conduit fittings

## Conduit couplings

Rigid fittings

### THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

#### Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

#### Features:

- NPSM threads

#### Standard materials:

- Heavy duty casting
- Malleable iron

#### Standard finish:

- Zinc plated

#### Options:

##### Description

- Hot dip galvanized .....**HDG**

##### Suffix

#### Malleable iron (concrete tight)

UL File No. E-19189



| Cat. # | Size   | Unit qty. | Wt. lbs. per 100 |
|--------|--------|-----------|------------------|
| 190M   | 1/2"   | 25        | 23               |
| 191    | 3/4"   | 25        | 35               |
| 192    | 1"     | 10        | 60               |
| 193    | 1 1/4" | 5         | 91               |
| 194    | 1 1/2" | 5         | 167              |
| 195    | 2"     | 5         | 215              |
| 196    | 2 1/2" | 2         | 430              |
| 197    | 3"     | 1         | 463              |
| 198    | 3 1/2" | 1         | 655              |
| 199    | 4"     | 1         | 800              |
| 188Ⓞ   | 5"     | 1         | 1200             |
| 189Ⓞ   | 6"     | 1         | 2100             |

Ⓞ Not UL Listed.

### THREE-PIECE CONDUIT COUPLINGS – ALUMINUM

#### Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

#### Features:

- NPSM threads

#### Standard materials:

- Aluminum

#### Standard finish:

- Natural

#### Aluminum (concrete tight)

UL File No. E-19189



| Cat. # | Size   | Unit qty. | Wt. lbs. per 100 |
|--------|--------|-----------|------------------|
| 190SA  | 1/2"   | 25        | 7                |
| 191SA  | 3/4"   | 25        | 9                |
| 192SA  | 1"     | 10        | 18               |
| 193SA  | 1 1/4" | 5         | 31               |
| 194SA  | 1 1/2" | 5         | 41               |
| 195SA  | 2"     | 5         | 64               |
| 196SA  | 2 1/2" | 2         | 95               |
| 197SA  | 3"     | 1         | 113              |
| 198SA  | 3 1/2" | 1         | 201              |
| 199SA  | 4"     | 1         | 253              |