

TECHNICAL DATA SHEET LOW VOLTAGE POWER CABLE

Cable Description:


Cu / XLPE / SWA / PVC 1kV 4X185 mm² SM
IEC 60502-1 FR-IEC 60332-1

Design and Construction Data:		
Reference Manufacturing Standards		IEC/BS EN 60228, IEC 60502-1
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	250
Rated Voltage 'U ₀ / U'	kV	0.6 / 1.0
Number of Conductors x Cross-Section	mm ²	4 x 185
Conductor Material & Shape		Copper & Stranded Class 2 Compacted Sector Shape
Insulation Material		XLPE
Conductor Nominal Insulation Thickness	mm	1.60
Insulation Color		RED, YELLOW, BLUE, BLACK
Armour Material Type		Galvanized Steel Wire
Outer Sheath Material		PVC - ST2
Colour of Outer Sheath		BLACK
Approximate Cable Overall Diameter	mm	53.9
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	0.0991
Max Conductor AC resistance @ 90 °C	ohms/km	0.1293
Max Conductor Short Circuit Current @ 1 Second	kA	26.46
Current Carry Capacity		
Laid in air @ 40 °C Ambient Temperature		
Free In Air	A	420
Laid in Ground		
Direct Laid	A	387
Laid in Ground with the following conditions: Ambient Ground Temperature: 35 °C Depth of laying in ground: 0.5 m Soil Thermal Resistivity: 1.2 °K.m/W		
Additional Data:		
Maximum pulling Tension	kN	37.00
Maximum side wall pressure	kN/m	85.8
Minimum Bending Radius	mm	431
The Cable shall meet all Test requirements of: IEC/BS EN 60228, IEC 60502-1, IEC 60332-1		
Packing Data:		
Drum Type		Non-Returnable
Length of Cable per drum (± 5%)	m	500
Drum Dimensions "Height x Width" (Approx.)	m	2 x 1.19
Gross Weight (Approximate without Lagging)	kg	5198

TECHNICAL DATA SHEET LOW VOLTAGE POWER CABLE

Cable Marking:

BAHRA CABLES CO. KSA 4 X 185 mm² Cu / XLPE / SWA / PVC 600 / 1000 V IEC 60502-1 FR IEC 60332-1
Manufacturing Year - Meter marked

Cable Drawing


Description	Cu / XLPE / SWA / PVC 1kV 4X185 mm ² SM	Approx. Diameter
1	Non-Hygroscopic Filler	-
2	Core	
	Stranded Copper Conductor with sectored shape	21.07 X 15.06
	XLPE insulated	24.27 X 18.26
3	Polymeric Tape	41.44
4	PVC Compound	43.95
5	Galvanized Steel Wire Armour (SWA)	48.75
6	PVC Outer Sheathing	53.89