



ENCLOSURES AND EQUIPMENT

- IP65 ENCLOSURE
- OUT DOOR / INDOOR APPLICATION
- SINGLE / DOUBLE DOOR

25 Direct
Immediate
Reliable
At No Cost

800-124-3472

* ضمان المنتجات الإلكترونية 3 سنوات فقط
Electronic Products Warranty is 3 years only

صنع في السعودية
Made in KSA

SERVICE ENCLOSURES



APPLICATIONS

Bahra Enclosures are designed to accommodate various type of switchgear and controlgear assemblies suitable to all types of electrical installations especially for commercials and industrial sectors. They are designed for outdoor applications up to IP-65.

SPECIFICATIONS

- Made of high CR and GI steel sheet of thickness up to 1.2-1.5 mm Max.
- Matt-finished polyester epoxy powder coated in RAL 7035 color.
- Standard GI mounting plate with 2.0mm thickness with holes provision for earthing.
- Double door for the width more than 800mm are composed of swing handle with three point latch lock.
- Corner formed door to insure better water protection and gives aesthetic look.
- Perforated door stiffeners for more rigidity and for easy cabling and fixing accessories.
- Special profiled enclosure lip for better liquid protections.
- Complies with IEC60529 & IEC 62208 standards.

CHARACTERISTICS



Single door quarter turn cylindrical lock with metal locking mechanism for durability



Removable gland plate at the bottom side with neoprene gasket to secure IP protection rating.



Concealed door hinges giving up to 120 degrees opening



Wall mounting brackets (Optional)



CNC Machine formed polyurethane gasket for door reliable sealing



Earthing studs are provided on both enclosure and door.



WALL MOUNTING ENCLOSURE

SEQ	ITEM NO	HEIGHT	WIDTH	DEPTH	DOOR
1	BHME202015	200	200	150	ONE
2	BHME252015	250	200	150	ONE
3	BHME303015	300	300	150	ONE
4	BHME302515	300	250	150	ONE
5	BHME302015	300	200	150	ONE
6	BHME303020	300	300	200	ONE
7	BHME302520	300	250	200	ONE
8	BHME403020	400	300	200	ONE
9	BHME403015	400	300	150	ONE
10	BHME404015	400	400	150	ONE
11	BHME504020	500	400	200	ONE
12	BHME504015	500	400	150	ONE
13	BHME504025	500	400	250	ONE
14	BHME604020	600	400	200	ONE
15	BHME604015	600	400	150	ONE
16	BHME604025	600	400	250	ONE
17	BHME605015	600	500	150	ONE
18	BHME605020	600	500	200	ONE
19	BHME605025	600	500	250	ONE
20	BHME606020	600	600	200	ONE
21	BHME705020	700	500	200	ONE
22	BHME706020	700	600	200	ONE
23	BHME705025	700	500	250	ONE
24	BHME806020	800	600	200	ONE
25	BHME806025	800	600	250	ONE
26	BHME806030	800	600	300	ONE
27	BHME808020	800	800	200	ONE
28	BHME808025	800	800	250	ONE
29	BHME1D108025	1000	800	250	ONE
30	BHME1D108030	1000	800	300	ONE
31	BHME1D106025	1000	600	250	ONE
32	BHME1D106020	1000	600	200	ONE
33	BHME1D108020	1000	800	200	ONE
34	BHME2D121030	1200	1000	300	TWO
35	BHME1D128030	1200	800	300	ONE