


TECHNICAL DATA SHEET LOW VOLTAGE THHN BUILDING WIRE

Cable Description:

16 AWG CU / PVC (THHN)

Design and Construction Data:		
Reference Manufacturing Standards		American Designation
Max. Permissible Continuous Conductor Temp	°C	105
Max. Conductor Short Circuit Temp for 5 Seconds	°C	150
Rated Voltage	V	600
Conductor Size	AWG	16
Number of wires per conductor		19
Wires Combination		Round Wires Unilay-Stranded
Insulation Material		Polyvinyl Chloride (PVC)
Nominal Insulation Thickness	mm	0.38
Insulation Color		RED
Outer Nylon Jacket		Polyamide Nylon
Approximate Wire Overall Diameter	mm	2
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	13.1000
Max Conductor AC resistance @ 90 °C	ohms/km	16.7000
Max Conductor Short Circuit Current @ 1 Second	kA	0.1220
Current Carry Capacity @ 30 °C Ambient Temperature ⁽¹⁾		
Single-Insulated Conductor		
Laid in free air	A	24
Not more than Three Current-Carrying Conductors ⁽²⁾		
Laid in Race way, Cable, or Earth "Directly Buried"	A	18
(i) - Ampacity based on NEC Table 310.15(B)(16) (Formerly Table 310.16) & Table 310.15(B)(17) (Formerly Table 310.17) - Refer to 310.15(B)(2)(a) for the ampacity correction factors where the ambient temperature is other than 30°C. - See Section 240.4 (D) for conductor overcurrent protection limitations. (ii) Refer to 310.15(B)(3)(a) for more than three current-carrying conductors The wire is generally according to: THHN designation		
Packing Data:		
Type		Spool
Length of Cable per Spool (± 2%)	m	152
Gross Weight (Approximate)	kg	3
Cable Marking:		
BAHRA CABLES CO. KSA THHN / THWN 16 AWG 600 Volts VW-1 GASOLINE & OIL RESISTANT II 105 ° C		
Cable Drawing		
		
Description	16 AWG CU / PVC (THHN)	Approx. Diameter
1	Copper conductor with round shape	1.5
2	PVC Insulation	2.26
3	Polyamide Nylon Jacketing	2.46