


TECHNICAL DATA SHEET LOW VOLTAGE BUILDING WIRE

Cable Description:

Cu / PVC 450 / 750 V H07V2-R 90 °C 1.5 mm² RM BLUE

Design and Construction Data:		
Reference Manufacturing Standards		IEC 60228, IEC 60227-3, BS EN 50525-2-31
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	160 °C
Rated Voltage	V	450 / 750
Conductor Size	mm ²	1.5
Conductor Material & Shape		Copper & Stranded Class 2 non-compacted Round Shape
Insulation Material		PVC
Nominal Insulation Thickness	mm	0.70
Insulation Color		LIGHT BLUE
Approximate Wire Overall Diameter	mm	2.9
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	12.1000
Max Conductor AC resistance @ 90 °C (Two/Three) Conductors	ohms/km	15.4287 / 15.4287
Max Conductor Short Circuit Current @ 1 Second	KA	0.15
Current Carry Capacity @ 30 °C Ambient Temperature		
Enclosed in conduit ⁽¹⁾		
Two Insulated Conductors Single Phase ac or dc	A	20
Three or Four Insulated Conductors Three Phase ac	A	18
Clipped direct ⁽²⁾		
Two Insulated Conductors Single Phase ac or dc	A	23
Three or Four Insulated Conductors Three Phase ac	A	21
(1) Current carrying capacity based on IEE wiring regulation method B cables single ac or dc / three phase ac, enclosed in conduit on a wall or in trunking etc. at 30 °C ambient temperature". (2) Current carrying capacity based on IEE wiring regulation method C cables single ac or dc / three phase , clipped direct at 30 °C ambient temperature". * ref (IEE Wiring Regulations 17th edition Table 4D1A)		
The Cable shall meet all Test requirements of: IEC/BS EN 60228, IEC 60227-3, BS EN 50525-2-31, IEC 60332-1		
Packing Data:		
Type		Coil
Length of Cable per Coil (± 2%)	m	92
Net Weight (Approximate)	kg	1.9
Cable Marking:		
BAHRA CABLES CO. KSA 1.5 MM ² CU/PVC 90 DEG C 450 / 750 V H07V2-R BS EN 50525-2-31 SASO 1320 TYPE 60227 IEC 01 FR IEC 60332-1		
Cable Drawing		
		
Description	Cu / PVC 450 / 750 V H07V2-R 90 °C 1.5 mm ² RM BLUE	Approx. Diameter
1	Copper conductor with round shape	1.52
2	PVC TI-3 Insulation	2.92