



8 332 97



8 334 89



8 330 69



8 332 59



8 330 44

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	RCD sockets 13 A - 250 V~	Pack	Cat.Nos	Socket outlets 15 A - 127 V~
		Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep ELO - DP 30 mA Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools			For flush-mounting, back box to be min. 35 mm deep 1 gang Nominal plate dimensions: 86 x 86 mm
1	8 330 85	AVAILABLE JULY 2016 1 gang - Nominal plate dimensions: 86 x 86 mm ● Brushed stainless steel	1	8 330 99	● Polished stainless steel
1	8 332 85	● Glossy gold	1	8 334 99	2 gang Nominal plate dimensions: 86 x 146 mm
1	8 334 85	● Brushed stainless steel	1	8 332 99	● Polished stainless steel
1	8 330 97	2 gang - Nominal plate dimensions: 86 x 146 mm ● Brushed stainless steel	1	8 331 99	● Glossy gold
1	8 332 97	● Polished stainless steel	1	8 335 99	Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 25 mm deep 1 gang unswitched Nominal plate dimensions: 86 x 86 mm
1	8 334 97	● Glossy gold	1	8 330 68	● Brushed stainless steel
		ELR - DP 30 mA Trips in the event of a power failure Ideal for applications where it is desirable to automatically re-activate equipment after a power failure. E.g. fridge, freezer, unmanned areas	1	8 332 68	● Polished stainless steel
1	8 330 86	AVAILABLE JULY 2016 1 gang - Nominal plate dimensions: 86 x 86 mm ● Brushed stainless steel	1	8 334 68	● Glossy gold
1	8 332 86	● Polished stainless steel	1	8 330 69	1 gang switched - single pole Nominal plate dimensions: 86 x 146 mm
1	8 334 86	● Glossy gold	1	8 332 69	● Brushed stainless steel
1	8 330 98	2 gang - Nominal plate dimensions: 86 x 146 mm ● Brushed stainless steel	1	8 334 69	● Polished stainless steel
1	8 332 98	● Polished stainless steel			Socket outlets 2 A - 250 V~ Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang unswitched Nominal plate dimensions: 86 x 86 mm
1	8 334 98	● Glossy gold	1	8 330 59	● Brushed stainless steel
		Socket outlets 15 A - 250 V~ Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm	1	8 332 59	● Polished stainless steel
1	8 330 88	1 gang unswitched ● Brushed stainless steel	1	8 334 59	● Glossy gold
1	8 332 88	● Polished stainless steel			Double USB sockets For flush-mounting, back box to be min. 40 mm deep Input voltage: 110 V/ 230 V Comply with IEC 62684 5 V (output) - 2400 mA Wiring with 1.5 Sq.mm and 2.5 Sq.mm (only live and neutral)
1	8 334 88	● Glossy gold	1	8 330 44	● Brushed stainless steel
1	8 330 89	1 gang switched - single pole ● Brushed stainless steel	1	8 332 44	● Polished stainless steel
1	8 332 89	● Polished stainless steel	1	8 334 44	● Glossy gold
1	8 334 89	● Glossy gold			