

Arteor™

international socket outlets (continued)



5 725 66



5 721 32








5 720 70 + plate 5 753 00





5 721 00



Support frame and plate selection charts **p. 594-603**

Pack	Cat.Nos	South African type socket outlets - 16 A
		2P+E unswitched - 1 module Conform to SANS 164-2 Mechanisms supplied with rocker plates, to be equipped with support frames (p. 585) and plates (p. 594-603)
10	5 721 36	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
10	5 726 36	
10	5 726 48	
10	5 721 48	
		2 new RSA socket outlets (164-2) and 1 old RSA switched socket outlet (164-1) Prewired, monobloc, 4x4 Supplied with support frame and rocker plate, to be equipped with 2x3 modules plate
1	5 720 66	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
1	5 725 66	
1	5 710 92	
1	5 700 90	
		2P+E - shuttered for child safety - 2 modules Mechanisms supplied with rocker plates, to be equipped with support frames (p. 585) and plates (p. 594-603)
10	5 721 22	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu ● Red
10	5 726 22	
10	5 724 26	
10	5 724 25	
10	5 724 61	
		2P+E switched - shuttered for child safety - 3 modules Mechanisms supplied with rocker plates, to be equipped with support frames (p. 585) and plates (p. 594-603)
5	5 721 32	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu ● Red dedicated
5	5 726 32	
5	5 724 28	
5	5 724 27	
5	5 724 65	
		2 x 2P+E switched - pre-wired - 2-gang Supplied with support frame and rocker plate, to be equipped with 2x3 modules plate
1	5 720 22	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
1	5 725 22	
1	5 700 22	
1	5 710 22	

Pack	Cat.Nos	South African type socket outlets - 16 A with USB charger
		All switched new RSA socket outlet (164-2) and old RSA socket outlet (164-1) Prewired, monobloc, 4x4 Supplied with support frame and rocker plate, to be equipped with 2x3 modules plate USB Type-A + Type-C, 3 A - 5 V _{DC} - 15 W Consumption of USB in passive mode < 0,08 W (when switched) The main switch controls the two RSA socket outlets and the double USB charger
1	5 720 70	 <ul style="list-style-type: none"> ○ White ● Magnesium ● Champagne ● Soft Alu
1	5 725 70	
1	5 710 93	
1	5 700 91	
		ELV socket outlets 3 A
		2P Mechanisms supplied with rocker plates, to be equipped with support frames (p. 585) and plates (p. 594-603) 12 mm fixing centres for plug Cat.No 0 500 05 1 module
10	5 721 00	 <ul style="list-style-type: none"> ○ White ● Magnesium
10	5 726 00	
		Plug 2P - 3 A for ELV socket outlet 12 mm fixing centres pins ø3.6 mm
20	0 500 05	