

Arteor™ television sockets



5721 72



5726 72

Support frames and plates selection chart (p. 118 to 125)

Mechanisms supplied with White or Magnesium square cover plates
To be equipped with support frames (p. 92-93) and plates (p. 94 to 125)

Pack	Cat.Nos		Television sockets
			For aerial and satellite installation (with individual demodulator) DTT and HDTV compatible TV: male connector (ø9.5 mm) attenuation ≤ 1.5 db R: female connector (ø9.5 mm) attenuation ≤ 1.5 db SAT: "F" type connector attenuation ≤ 2 db Recommended coaxial cable: 17/19 VATC
10	5721 63	5726 63	TV sockets TV single shielded "F" type with screws 0-2400 MHz 1 module 22.5 x 45 mm
10	5721 71	5726 71	TV single shielded male ø9.5 mm 0-2400 MHz 1 module 22.5 x 45 mm
10	5721 70	5726 70	TV-R socket TV-R shielded socket female-male ø9.5 mm 2 modules 22.5 x 45 mm
10	5721 72	5726 72	TV-R-SAT socket TV-R-SAT shielded socket 0-2400 MHz 2 modules 22.5 x 45 mm
1	5721 80	5726 80	TV socket for Singapore For cable vision 2 modules 22.5 x 45 mm

Arteor™ telephone sockets



5723 00



5728 13

Support frames and plates selection chart (p. 118 to 125)

Mechanisms supplied with White or Magnesium square cover plates
To be equipped with support frames (p. 92-93) and plates (p. 94 to 125)

Pack	Cat.Nos		RJ 11 and RJ 12 sockets
			Equipped with modular Jack connector with 1/4 turn terminal for fast connection (possible looping)
10	5723 00	5728 00	RJ 11 4 contacts 1 module 22.5 x 45 mm
10	5723 13	5728 13	4 contacts 2 modules 22.5 x 45 mm
10	5723 12	5728 12	RJ 12 6 contacts 2 modules 22.5 x 45 mm
			Telephone sockets With IDC connection Conform to British Telecom
10	5723 10	5728 10	Single master 2 modules 22.5 x 45 mm
5	5723 01	5728 01	Single secondary 1 module 22.5 x 45 mm