CAT. N° 0 522 34



PANEL MOUNTING SOCKET INCLINED OUTLET HYPRA - IP44 -380/415 V -16 A -3P+N+E -METAL

Pack (number of units)	1
Volume (dm³)	0,869
Weight (g)	502,00

Product characteristics

LV panel mounting sockets

380 to 415 V~ 50/60 Hz - 16 A 3P+N+E

- To be associated with box Cat.No 0 522 29 for surface-mounting socket or Cat.No 0 522 89 for through wiring surface mounting socket
- Metal
- 16 A

General characteristics

Hypra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prisinter - LV 16 to 63 A and ELV 16 and 32 A

- Conform to IEC 60309-1 and IEC 60309-2
- IP 44 according to IEC 60529
- IK 09: plastic and rubber
- IK 10: metal according to IEC 62262
- Self-extinguishing:
  - 850°C (support of active parts) / 960 °C for Prinsinter)
  - 650 °C: plastic housing conform to IEC 60695-2-10
  - 50°C to + 100°C (- 20°C for Prisinter)

Documentation

Catalogue pages & additional information

- Selection chart (p.390-391)
- Technical page (p.392)
- Hypra

Agreements & certificates of conformity

- OC / CB - FR_710635/A1

Installation & technical data

- F00138EN-03

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.