

# Product sheet



## MALLIA SENSES LEGRAND

Mallia Senses 1 gang key card switch 12 volts

REF. 281022BB | EAN. 3414972059831

**No price to display**

> [Visit e-catalogue](#)

## Product characteristics

- 12V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Brushed black finish

## Recommendations / Restrictions

- Recommended inside use only

## The product's benefits

### Usage

- Homogeneous hotel offer

### Advantages

- RFID technology to secure access
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

## Technical characteristics

Assembly arrangement	Basic element with full cover plate
Model	Relay
Type of load	Other
Substation input	No
Light value memory	No
Applicable with button	No
Applicable with movement sensor	No
Applicable with presence indicator	No
Applicable with time switch/timer	Yes
Applicable with transmission button	No
Applicable with infrared button	No

Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Width	86 mm
Height	46.5 mm
Depth	86 mm
Built-in depth	32.2 mm
Degree of impact strength (IK)	IK04
Degree of protection (IP)	IP20
Operating / setting temperature	-5-35 °C
Storage temperature	-20-70 °C

<b>Mounting method</b>	Flush-mounted
<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic
<b>Surface protection</b>	Untreated
<b>Surface finishing</b>	Matt
<b>Colour</b>	Black
<b>Transparent</b>	No
<b>Nominal voltage</b>	12 V
<b>Number of channels</b>	1
<b>Type of fastening</b>	Mounting with screw
<b>Min. depth of built-in installation box</b>	40 mm
<b>Compatible with Apple HomeKit</b>	No

<b>Standby consumption</b>	16.7 mA
<b>Mandatory neutral</b>	No
<b>Terminal marking indication</b>	Yes
<b>Halogen free</b>	Yes
<b>Antimicrobial treatment</b>	No
<b>Connection type</b>	Screwed terminal
<b>Number of terminals</b>	4
<b>Terminals capacity</b>	1-4 mm <sup>2</sup>
<b>Cable section</b>	1-4 mm <sup>2</sup>
<b>Label space/information surface</b>	No
<b>Contains Batteries and/or Accumulator</b>	No
<b>Connected object</b>	No

## Documentation

### TECHNICAL DOCUMENTATION

 [F03248EN-00.pdf](#) | PDF (0.43Mo)

### Agreements & Certificates

 [OC CEM / CB EMC-ARLI-ESH-P21030500B-R1](#) | (0.24Mo)