

# Product sheet



## MALLIA SENSES LEGRAND

Mallia Senses - 2 gang push-button 10A - Brushed Black

REF. 281042BB | EAN. 3414972079280

The double push-button is suitable for several everyday uses : lighting, door opening, door bell, timer..

**No price to display**

> [Visit e-catalogue](#)

## Description

The double push-button is suitable for several everyday uses : lighting, door opening, door bell, timer..

### Product characteristics

- 10A, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Brushed black finish

### Recommendations / Restrictions

- Recommended inside use only

## Technical characteristics

Assembly arrangement	Basic element with complete housing
Model	Single push button
Method of operation	Rocker
Contactless type	No
Number of rockers	2
Number of poles	1
Nominal voltage	250 V
Rated current	10 A
With lighting	No

Label space/information surface	Yes
Imprint	None
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Device width	86 mm
Device height	86 mm
Device depth	34.6 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No

## The product's benefits

### Installation

- Quick and Easy plate-rocker clipping system

### Usage

- Homogeneous hotel offer

### Advantages

- A definite motion with a subtle touch on the rocker
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

<b>With light source</b>	No
<b>Feedback-signal contact</b>	No
<b>Connection type</b>	Screwed terminal
<b>Mounting method</b>	Flush-mounted
<b>Type of fastening</b>	Screw mounting
<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic
<b>Halogen free</b>	Yes
<b>Antimicrobial treatment</b>	No
<b>Surface protection</b>	Untreated
<b>Surface finishing</b>	Matt
<b>Colour</b>	Black
<b>Transparent</b>	No

<b>Compatible with Google Assistant</b>	No
<b>Compatible with Amazon Alexa</b>	No
<b>IFTTT support available</b>	No
<b>Built-in depth</b>	24.9 mm
<b>Operating / setting temperature</b>	-5-50 °C
<b>Storage temperature</b>	-10-70 °C
<b>Voltage type</b>	AC
<b>Frequency</b>	50-60 Hz
<b>Mandatory neutral</b>	Yes
<b>Terminal marking indication</b>	Yes
<b>Terminals capacity</b>	1-4 mm <sup>2</sup>
<b>Cable nature for connection</b>	Flexible or rigid
<b>Cable section</b>	1-4 mm <sup>2</sup>

## Documentation

### TECHNICAL DOCUMENTATION

[F03225EN-00.pdf](#) | PDF (0.52Mo)

### Agreements & Certificates

[OC / CB-CN52793-M2](#) | (0.66Mo)

[OC / CB-CN52793-M1](#) | (0.64Mo)

[OC / CB-CN52793](#) | (0.33Mo)

### CATALOGUE PAGE & OTHERS

[ex223001\\_0690.pdf](#) | PDF (0.07Mo)