

# Product sheet



## MALLIA SENSES LEGRAND

Mallia Senses - 2 gang push-button 10A - Champagne

REF. 281042CH | EAN. 3414972079341

The double push-button is suitable for several everyday uses : lighting, door opening, door bell, timer..

**No price to display**

> [Visit e-catalogue](#)

## Description

The double push-button is suitable for several everyday uses : lighting, door opening, door bell, timer..

### Product characteristics

- 10A, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Champagne finish

### Recommendations / Restrictions

- Recommended inside use only

## Technical characteristics

<b>Assembly arrangement</b>	Basic element with complete housing
<b>Model</b>	Single push button
<b>Method of operation</b>	Rocker
<b>Contactless type</b>	No
<b>Number of rockers</b>	2
<b>Number of poles</b>	1
<b>Nominal voltage</b>	250 V
<b>Rated current</b>	10 A
<b>With lighting</b>	No

<b>Label space/information surface</b>	Yes
<b>Imprint</b>	None
<b>Suitable for degree of protection (IP)</b>	IP20
<b>Degree of impact strength (IK)</b>	IK04
<b>Device width</b>	86 mm
<b>Device height</b>	86 mm
<b>Device depth</b>	34.6 mm
<b>Min. depth of built-in installation box</b>	35 mm
<b>Compatible with Apple HomeKit</b>	No

## The product's benefits

### Installation

- Quick and Easy plate-rocker clipping system

### Usage

- Homogeneous hotel offer

### Advantages

- A definite motion with a subtle touch on the rocker
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

<b>With light source</b>	No
<b>Feedback-signal contact</b>	No
<b>Connection type</b>	Screwed terminal
<b>Mounting method</b>	Flush-mounted
<b>Type of fastening</b>	Screw mounting
<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic
<b>Halogen free</b>	Yes
<b>Antimicrobial treatment</b>	No
<b>Surface protection</b>	Untreated
<b>Surface finishing</b>	Matt
<b>Colour</b>	Other
<b>Transparent</b>	No

<b>Compatible with Google Assistant</b>	No
<b>Compatible with Amazon Alexa</b>	No
<b>IFTTT support available</b>	No
<b>Built-in depth</b>	24.9 mm
<b>Operating / setting temperature</b>	-5-50 °C
<b>Storage temperature</b>	-10-70 °C
<b>Voltage type</b>	AC
<b>Frequency</b>	50-60 Hz
<b>Mandatory neutral</b>	Yes
<b>Terminal marking indication</b>	Yes
<b>Terminals capacity</b>	1-4 mm <sup>2</sup>
<b>Cable nature for connection</b>	Flexible or rigid
<b>Cable section</b>	1-4 mm <sup>2</sup>

## Documentation

### TECHNICAL DOCUMENTATION

F03225EN-00.pdf | PDF (0.52Mo)

### Agreements & Certificates

OC / CB-CN52793-M2 | (0.66Mo)

OC / CB-CN52793-M1 | (0.64Mo)

OC / CB-CN52793 | (0.33Mo)

### CATALOGUE PAGE & OTHERS

ex223001\_0690.pdf | PDF (0.07Mo)