

Product sheet



MALLIA SENSES LEGRAND

Mallia Senses - 1 gang Do Not Disturb and Make Up my Room and bell push-button - Champagne

REF. 281045CH | EAN. 3414972070539

Door bell and indicator (with light colors) to be installed in the corridor: shows the presence of a guest in a room and his/her needs.

No price to display

> [Visit e-catalogue](#)

Description

Door bell and indicator (with light colors) to be installed in the corridor: shows the presence of a guest in a room and his/her needs.

Product characteristics

- 6A, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Champagne finish

Recommendations / Restrictions

- Recommended inside use only

Technical characteristics

Assembly arrangement	Basic element with adapter plate
Model	Single push button
Method of operation	Push button
Contactless type	Yes
Number of rockers	1
Number of modules (module system)	2
Nominal voltage	240 V
Rated current	3 A
With lighting	Yes

Label space/information surface	No
Imprint	Symbol "bell"
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Device width	86 mm
Device height	86 mm
Device depth	39.7 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No

The product's benefits

Installation

- Quick and Easy plate-rocker clipping system

Usage

- Homogeneous hotel offer

Advantages

- A definite motion with a subtle touch on the rocker
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

With light source	No
Feedback-signal contact	No
Connection type	Screwed terminal
Mounting method	Flush-mounted
Type of fastening	Screw mounting
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Matt
Colour	Other
Transparent	No

Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Built-in depth	30 mm
Operating / setting temperature	-20-70 °C
Storage temperature	-5-35 °C
Voltage type	AC
Frequency	50-60 Hz
Mandatory neutral	Yes
Terminal marking indication	Yes
Terminals capacity	1-4 mm ²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm ²

Documentation

TECHNICAL DOCUMENTATION

[LE12392AA.pdf](#) | PDF (0.86Mo)

[F03226EN-00.pdf](#) | PDF (0.51Mo)

Agreements & Certificates

[OC / CB-FR_713380](#) | (0.36Mo)

CATALOGUE PAGE & OTHERS

[ex223001_0701.pdf](#) | PDF (0.08Mo)