

# Product sheet



## MALLIA SENSES LEGRAND

Mallia Senses - 1 gang 1 way double pole switch 20AX - Brushed Aluminium

REF. 281060BA | EAN. 3414972062879

Allows to control lighting, with a smooth and soft touch on the rocker

**No price to display**

> [Visit e-catalogue](#)

## Description

Allows to control lighting, with a smooth and soft touch on the rocker

### Product characteristics

- 20AX, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Brushed aluminium finish

### Recommendations / Restrictions

- Recommended inside use only

## The product's benefits

### Installation

- Quick and Easy plate-rocker clipping system

### Usage

- Complies with British Standards certifications for heavy loads

### Advantages

- Definite motion for a soft touch and sound
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

## Technical characteristics

<b>Wiring system</b>	Off switch 2x1-pole
<b>Method of operation</b>	Rocker lever
<b>Assembly arrangement</b>	Basic element with full cover plate
<b>Push button switch</b>	No
<b>Number of rockers</b>	1
<b>Mounting method</b>	Flush-mounted
<b>Type of fastening</b>	Screw mounting
<b>With mounting plate</b>	Yes

<b>Feedback-signal contact</b>	No
<b>Connection type</b>	Screwed terminal
<b>Heating switch</b>	No
<b>Washing machine switch</b>	No
<b>Device width</b>	86 mm
<b>Device height</b>	86 mm
<b>Device depth</b>	41.1 mm
<b>Built-in depth</b>	29.6 mm

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Metallic
Surface finishing	Matt
Colour	Aluminium
Colour of switch operator	Aluminium
Illumination	No
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX

Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Frequency	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Terminals capacity	1-4 mm <sup>2</sup>
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm <sup>2</sup>

## Documentation

### TECHNICAL DOCUMENTATION

F03222EN-01.pdf | PDF (0.49Mo)

### Agreements & Certificates

OC / CB-CN54082-M1 | (0.64Mo)

OC / CB-CN54082 | (0.62Mo)

### CATALOGUE PAGE & OTHERS

ex223001\_0688.pdf | PDF (0.07Mo)