

Product sheet



MALLIA SENSES LEGRAND

Mallia Senses - 1 gang 1 way double pole switch with red power indicator - 32A - Dark Bronze

REF. 281074DB | EAN. 3414972064309

Allows to control a heavy load up to 32A. One gang plate featuring red light indicator

No price to display

> [Visit e-catalogue](#)

Description

Allows to control a heavy load up to 32A. One gang plate featuring red light indicator

Product characteristics

- 32A, 250V
- MALLIA SENSES is sold as a complete set under one cat number
- Red indicator on the rocker
- Marked terminals for easy identification
- Dark bronze finish

Recommendations / Restrictions

- Recommended inside use only

Technical characteristics

Wiring system	Off switch 2x1-pole
Method of operation	Rocker lever
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes

The product's benefits

Installation

- Quick and Easy plate clipping system

Usage

- No accessible electrical contact under the rocker.

Advantages

- Delivered with its protective shell against paint and dust during installation phase
- Technicity and Robustness of the support frame
- Thin and modern design for a perfect decoration integration

Feedback-signal contact	No
Connection type	Screwed terminal
Heating switch	No
Washing machine switch	No
Device width	86 mm
Device height	86 mm
Device depth	34.1 mm
Built-in depth	22.8 mm

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Lacquered
Surface finishing	Matt
Colour	Bronze
Colour of switch operator	Red
Illumination	Yes
Function lighting	Illuminated (on)
Type of lighting	LED not exchangeable
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	32 A

Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature	-5-50 °C
Storage temperature	-10-70 °C
Voltage type	AC
Frequency	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Terminals capacity	1-4 mm ²
Cable nature for connection	Flexible or rigid
Cable section	1-4 mm ²

Documentation

TECHNICAL DOCUMENTATION

F03223EN-00.pdf | PDF (0.46Mo)

Agreements & Certificates

OC / CB-CN48869-A1/M3 | (0.95Mo)

OC / CB-CN48869-A1/M2 | (0.79Mo)

CATALOGUE PAGE & OTHERS

ex223001_0689.pdf | PDF (0.08Mo)