

201.CS2424-5**CHARGING CABLE**

T2 32A 3P - T2 32A 3P
5G6+1x0,5mm² 5m 22kW



EN 50620 (2017)
EN 62196-2 (2017)
EN 62196-1 (2014)
EN 50620/A1 (2019)

Low voltage direct. 2014/35/EU

Commercial Series	LIBERA[CS] Series
Synthetical description	CHARGING CABLE
EV standard	Type 2 3P+N+E 32A 400V~ 22kW

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Rated voltage	400V
Max power	22kW
Cable section	5G6+1x0,5mm ²

■ PHYSICAL CHARACTERISTICS

Protection degree IP	IP44
Material	THERMOPLASTIC
Working temperature	-30°C/+50°C

■ DIMENSIONAL CHARACTERISTICS

Cable length	5m
--------------	----

■ INTERFACE, CONTROLS, FUNCTIONS AND EQUIPMENT

EV standard	Type 2 3P+N+E 32A 400V~ 22kW
EV plug	Type 2 3P+N+E 32A 400V~
EV connector	Type 2 3P+N+E 32A 400V~

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

■ OPTIONS & VARIOUS NOTES

Notes	T2 32A 3P - T2 32A 3P
-------	-----------------------