

**218.3237RV****PLUG**

32A 3P+N+E 6h 346-415V 60Hz 50Hz  
Screw terminals With REVERSE  
device



EN 60309-1/A1 (2007)  
EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-2/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	OPTIMA-REVERSE Series
Synthetical description	PLUG
Mounting version	PORTABLE

#### ■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

#### ■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

#### ■ DOWNLOAD

Technical drawing [PDF]  
Technical drawing [DWG]  
Technical drawing [STP]

#### ■ OPTIONS & VARIOUS NOTES

Options	With REVERSE device
---------	---------------------