

**500.3283**

**INTERLOCKED SOCKET**  
**32A 2P+E 6h 200-250V 60Hz 50Hz**  
**136X125MM\_PAR Screw terminals**  
**With mechanical interlock**



EN 60309-2/A1 (2007)  
 EN 60309-1 (1999)  
 EN 60309-2 (1999)  
 EN 60309-1/A1 (2007)  
 EN 60309-1/A2 (2012)  
 EN 60309-2/A2 (2012)  
 EN 60309-4 (2007)  
 EN 60309-4/A1 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OMNIA Series

Synthetical description

INTERLOCKED SOCKET

Mounting version

SURFACE MOUNTING

### ■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

### ■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Contact material	CuZn (brass)

### ■ DIMENSIONAL CHARACTERISTICS

Flange	136X125MM_PAR
--------	---------------

### ■ DOWNLOAD

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)  
[Instruction manual](#)

### ■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER