

505.6387**INTERLOCKED SOCKET**

63A 3P+N+E 6h 346-415V 60Hz 50Hz
136X275MM_PAR Screw terminals
With mechanical interlock



EN 60309-4/A1 (2012)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60309-4 (2007)

Low voltage direct. 2014/35/EU

Commercial Series

OMNIA Series

Synthetical description

INTERLOCKED SOCKET

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)

■ DIMENSIONAL CHARACTERISTICS

Flange	136X275MM_PAR
--------	---------------

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER