

### 592.R002-03-P

SP TWO WAY SWITCH  
 SP TWO WAY SWITCH 16AX  
 1xM20+2xM20 II 2GD



EN 60079-31 (2014)  
 EN 60079-1 (2014)  
 EN 60079-7 (2015)  
 EN 60079-7/A1(2018)  
 IEC 60079-1 (2014)  
 IEC 60079-0 (2017)  
 IEC 60079-7 (2017)  
 IEC 60079-31 (2022)  
 EN 60669-1 (2018)  
 IEC 60669-1 (2017)  
 EN IEC 60079-0 (2018)  
 EN IEC 60079-31 (2024)  
 ATEX directive 2014/34/EU

Commercial Series	ROCKER-EX[GD] Series
Synthetical description	SP TWO WAY SWITCH
Mounting version	SURFACE MOUNTING

#### TECHNICAL CHARACTERISTICS

Rated current	16AX
Rated voltage	250V

#### EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

#### PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOPLASTIC
Protection degree IK	IK07
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C

#### DOWNLOAD

- Technical drawing [PDF]
- Technical drawing [DWG]
- Technical drawing [STP]
- Instruction manual
- Instruction manual
- Instruction manual

#### OPTIONS & VARIOUS NOTES

Notes	1xM20+2xM20
-------	-------------