



Panflex

FLEXIBLE STEEL CONDUIT



The flexible conduit is manufactured with a continuous spiral wound strip of corrosion rust resistant, hot dipped galvanized steel. Galvanized steel flexible conduit is suitable for concealed, exposed or approved raceways.

The natural color type RWS conduit features a smooth metal interior for easy wire pulling. The flexible steel conduit is wire temperature rated, and has superior crush proof qualities.

Applications:

- Motor Feeder, Branch, Control circuit conductors and cable
- Environmental air-handling spaces.
- Concealed or exposed installations
- Elevators, hoistways escalators

Benefits:

- Smooth interior for easy wire pulling
- Able to withstand high temperatures
- Durable crush-proof construction
- Corrosion and rust resistant

FLEXIBLE METAL CONDUIT—STEEL (WEIGHTS AND DIMENSIONS)

Code	Trade Size	Internal Diameter mm.		Outside Diameter mm.		Min. Bending Radius (mm)	Length of Conduit (M/Roll)	Weight (kg)
		Min.	Max.	Min.	Max.			
SFC012UL	½"	19.00	19.60	23.00	23.30	65	30	7.96
SFC034UL	¾"	23.10	23.70	27.40	27.80	75	30	9.78
SFC100UL	1"	27.30	27.90	33.60	33.90	100	15	6.56

Other Sizes are also available upon request