

CAT. N° 0 529 04



## PANEL MOUNTING SOCKET PRISINTER HYPRA - IP44 -380/415 V~ -32 A - 3P+N+E - PLASTIC

Pack (number of units)	1
Volume (dm <sup>3</sup> )	3,744
Weight (g)	725,00

### Product characteristics

#### LV prisinters

- Dust resistance IP may be increased by rubber push-button (on request)
- IP 55 cover closed or connected - IP 44 connected

#### 380 to 415 V~ 50/60 Hz - 32 A 3P+N+E

- To be associated with surface-mounting box Cat. No 0 529 49 for surface-mounting socket
- Panel mounting socket - plastic
- 32 A

### General characteristics

#### Hypra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prisinter - LV 16 to 63 A and ELV 16 and 32 A

- Conform to IEC 60309-1 and IEC 60309-2
- IP 44 according to IEC 60529
- IK 09: plastic and rubber
- IK 10: metal according to IEC 62262
- Self-extinguishing:
  - 850°C (support of active parts) / 960 °C for Prinsinter)
  - 650 °C: plastic housing conform to IEC 60695-2-10
  - 50°C to + 100°C (- 20°C for Prisinter)

### Documentation

#### Catalogue pages & additional information

- [Selection chart \(p.390-391\)](#)
- [Technical page \(p.392\)](#)
- [Hypra](#)

#### Agreements & certificates of conformity

- [OC / CB - FR\\_710634](#)

#### Installation & technical data

- [F00097EN-05](#)