

CAT. N° 0 529 49



## BOX HYBRA - IP44 - FOR PRISINTER SURFACE SOCKETS 2P+E/3P+E/3P+N+E - 32 A - METAL

|                           |        |
|---------------------------|--------|
| Pack (number of units)    | 1      |
| Volume (dm <sup>3</sup> ) | 2,006  |
| Weight (g)                | 364,00 |

### Product characteristics

#### Accessories

##### For LV prisinter

- Box Hybra
- For plastic prisinter:
  - 200 to 250 V~ 32 A 2P+E
  - 380 to 415 V~ 32 A 3P+E
  - 380 to 415 V~ 32 A 3P+N+E

### General characteristics

#### Hybra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prisinter - LV 16 to 63 A and ELV 16 and 32 A

- Conform to IEC 60309-1 and IEC 60309-2
- IP 44 according to IEC 60529
- IK 09: plastic and rubber
- IK 10: metal according to IEC 62262
- Self-extinguishing:
  - 850°C (support of active parts) / 960 °C for Prinsinter)
  - 650 °C: plastic housing conform to IEC 60695-2-10
  - 50°C to + 100°C (- 20°C for Prinsinter)

### Documentation

#### Catalogue pages & additional information

- [Selection chart \(p.390-391\)](#)
- [Technical page \(p.392\)](#)
- [Hybra](#)

#### Installation & technical data

- [F00097EN-05](#)