


## Flexible Squeeze Connectors

### Straight - Squeeze Type - Zinc Die Cast



**Features**

- Squeeze type straight
- Available with insulated throat

**Applications**

- Indoor use only
- In a dry location, use to connect flexible metallic conduit to a steel outlet box, load center or other metal enclosure


**Standard Material**

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			Screws
					A	B (Min.-Max.)	C	
CFSC050	½"	25	250	25	1.47	0.74-0.95	.400	1
CFSC075	¾"	25	250	32	1.58	0.88-1.11	.400	1
CFSC100	1"	10	100	20	1.75	1.14-1.38	.540	1
CFSC125	1-¼"	10	100	29	1.91	1.42-1.65	.640	1
CFSC150	1-½"	5	50	20	2.09	1.68-1.94	.750	1
CFSC200	2"	10	40	21	2.34	2.08-2.56	.740	1
CFSC250	2-½"	—	10	9	2.81	2.85-3.25	.875	2
CFSC300	3"	—	10	17	3.84	3.33-3.63	1.03	2
CFSC350	3-½"	—	1	3	4.19	3.75-4.10	1.03	2
CFSC400	4"	—	1	3	4.56	4.18-4.58	1.03	2

\* Insulated models are also available. Please add "-I" to the part number while ordering (CFSC050I)

### 90° - Squeeze Type - Zinc



**Features**

- Squeeze type

**Applications**

- Indoor use only
- In a dry location, use to connect flexible metal conduit to a steel outlet box or other metal enclosure

**Standard Material**

- Zinc die cast
- Zinc plated steel strap

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			Screws
					A	B (Min.-Max.)	C	
CFSC9050	½"	25	250	35	2.110	0.64-1.03	.400	2
CFSC9075	¾"	10	100	20	2.400	0.76-1.15	.400	2
CFSC9100	1"	5	50	19	2.870	1.09-1.73	.540	2
CFSC9125	1-¼"	10	40	20	4.000	1.34-1.97	.640	2
CFSC9150	1-½"	---	5	5	6.000	1.65-2.61	.750	2
CFSC9200	2"	---	5	6	6.000	1.54-2.54	.740	2
CFSC9250	2-½"	---	5	18	7.187	2.45-2.98	.875	4
CFSC9300	3"	---	2	9	7.875	2.93-3.45	1.031	4
CFSC9350	3-½"	---	1	9	9.400	3.28-3.95	1.031	4
CFSC9400	4"	---	1	10	10.200	3.68-4.43	1.031	4

\* Insulated models are also available. Please add "-I" to the part number while ordering (CFSC9050I)