

# Rigid/intermediate grade conduit fittings

## Insulating & throat bushings

Rigid fittings

### THROAT BUSHINGS – MALLEABLE IRON

#### Threaded 105°C rated plastic throat liner

UL File No. E-19189



#### Insulated

Cat. #	Size	Unit qty.	Wt. lbs. per 100
1031	1/2"	100	3
1032	3/4"	100	4
1033	1"	50	7
1034	1 1/4"	50	15
1035	1 1/2"	10	19
1036	2"	20	22
1037	2 1/2"	10	44
1038	3"	10	54
1039	3 1/2"	5	72
1040	4"	5	95
1041	5"	1	100
1042	6"	1	127

#### Threadless 105°C rated plastic throat liner

UL File No. E-19189



Cat. #	Size	Unit qty.	Wt. lbs. per 100
S1031	1/2"	100	3
S1032	3/4"	100	4
S1033	1"	50	7
S1034	1 1/4"	50	15
S1035	1 1/2"	10	19
S1036	2"	20	22
S1037	2 1/2"	10	44
S1038	3"	10	54
S1039	3 1/2"	5	72
S1040	4"	5	95
S1041	5"	1	100
S1042	6"	1	127

### INSULATED THROAT BUSHINGS – MALLEABLE IRON

#### Features:

- Plastic liner will not chip, crack, swell or shrink; it resists corrosion, chemicals and temperature extremes

#### Standard materials:

- Body – malleable iron
- Insuliner – ULTEM1000 rated at 150°C

#### Standard finish:

- Body – zinc plated

#### Threaded 150°C rated

UL File No. E-19189



Cat. #	Size	Unit qty.	Wt. lbs. per 100
H1031	1/2"	100	6
H1032	3/4"	100	8
H1033	1"	50	11
H1034	1 1/4"	50	14
H1035	1 1/2"	10	17
H1036	2"	20	24
H1037	2 1/2"	10	51
H1038	3"	10	62
H1039	3 1/2"	5	85
H1040	4"	5	104
H1041	5"	1	130
H1042	6"	1	167

### INSULATED THROAT BUSHINGS

#### Threadless 150°C rated set screw type

UL File No. E-19189



Cat. #	Size	Unit qty.	Wt. lbs. per 100
HS1031	1/2"	100	6
HS1032	3/4"	100	7
HS1033	1"	50	10
HS1034	1 1/4"	50	13
HS1035	1 1/2"	10	15
HS1036	2"	20	21
HS1037	2 1/2"	10	42
HS1038	3"	10	51
HS1039	3 1/2"	5	65
HS1040	4"	5	80
HS1041	5"	1	100
HS1042	6"	1	128