

# Form 5

## Conduit outlet bodies, covers & gaskets – malleable iron

Form 5

### Options:

#### Description

- SnapPack™ – packaged body and integral gasket cover ..... **CG**  
Available on all configurations (1/2" - 2")

#### Suffix

### TYPE LB



Cat. #	Size	Internal vol. in cu. in.	Unit qty.	Wt. lbs. per 100	Max. no. of conductors
LB50M	1/2"	4.5	10	71	N/A
LB75M	3/4"	7.5	10	97	3 #6 AWG
LB100M	1"	12.5	10	143	3 #4 XHHW
LB125M <sup>M</sup>	1 1/4"	32.0	5	287	3 #2 XHHW
LB150M <sup>M</sup>	1 1/2"	35.3	5	331	3 #2 XHHW
LB200M <sup>M</sup>	2"	73.0	1	534	3 #4/0 XHHW
LB250M <sup>M</sup>	2 1/2"	142.0	1	1105	3 #300MCM XHHW
LB300M <sup>M</sup>	3"	173.0	1	1160	3 #400MCM XHHW
LB350M <sup>M</sup>	3 1/2"	292.0	1	1989	3 #500MCM XHHW
LB400M <sup>M,N</sup>	4"	324.0	1	2099	3 #500MCM XHHW

<sup>M</sup>1 1/4" - 4" LB and C bodies supplied with built-in rollers to facilitate wire pulling.  
<sup>N</sup>Self-certified to #500MCM XHHW.

### TYPE LL



Cat. #	Size	Internal vol. in cu. in.	Unit qty.	Wt. lbs. per 100	Max. no. of conductors
LL50M	1/2"	4.5	10	76	N/A
LL75M	3/4"	7.5	10	95	3 #6 AWG
LL100M	1"	12.5	10	138	3 #4 XHHW
LL125M	1 1/4"	32.0	5	309	3 #2 XHHW
LL150M	1 1/2"	33.0	5	332	3 #2 XHHW
LL200M	2"	68.0	1	497	3 #4/0 XHHW
LL250M	2 1/2"	142.0	1	1105	3 #300MCM XHHW
LL300M	3"	173.0	1	1437	3 #350MCM XHHW
LL350M	3 1/2"	292.0	1	2321	3 #350MCM XHHW
LL400M	4"	324.0	1	2431	3 #350MCM XHHW

### TYPE C



Cat. #	Size	Internal vol. in cu. in.	Unit qty.	Wt. lbs. per 100	Max. no. of conductors
C50M	1/2"	4.5	10	98	N/A
C75M	3/4"	7.5	10	118	3 #6 AWG
C100M	1"	12.5	10	170	3 #4 XHHW
C125M <sup>M</sup>	1 1/4"	35.0	5	309	3 #2 XHHW
C150M <sup>M</sup>	1 1/2"	35.3	5	368	3 #1/0 XHHW
C200M <sup>M</sup>	2"	75.0	1	552	3 #4/0 XHHW
C250M <sup>M</sup>	2 1/2"	153.0	1	1216	3 #300MCM XHHW
C300M <sup>M</sup>	3"	181.0	1	1437	3 #350MCM XHHW
C350M <sup>M</sup>	3 1/2"	290.0	1	2210	3 #350MCM XHHW
C400M <sup>M</sup>	4"	320.0	1	2321	3 #350MCM XHHW

<sup>M</sup>1 1/4" - 4" LB and C bodies supplied with built-in rollers to facilitate wire pulling.

### TYPE LR



Cat. #	Size	Internal vol. in cu. in.	Unit qty.	Wt. lbs. per 100	Max. no. of conductors
LR50M	1/2"	4.5	10	71	N/A
LR75M	3/4"	7.5	10	100	3 #6 AWG
LR100M	1"	12.5	10	157	3 #4 XHHW
LR125M	1 1/4"	32.0	5	332	3 #2 XHHW
LR150M	1 1/2"	35.3	5	345	3 #2 XHHW
LR200M	2"	68.0	1	626	3 #4/0 XHHW
LR250M	2 1/2"	142.0	1	1105	3 #300MCM XHHW
LR300M	3"	173.0	1	1437	3 #350MCM XHHW
LR350M	3 1/2"	292.0	1	2321	3 #350MCM XHHW
LR400M	4"	324.0	1	2500	3 #350MCM XHHW

### TYPE T



Cat. #	Size	Internal vol. in cu. in.	Unit qty.	Wt. lbs. per 100	Max. no. of conductors
T50M	1/2"	6.0	10	111	N/A
T75M	3/4"	9.5	10	137	3 #6 AWG
T100M	1"	15.0	10	196	3 #4 XHHW
T125M	1 1/4"	33.0	5	332	3 #2 XHHW
T150M	1 1/2"	36.0	5	368	3 #1 XHHW
T200M	2"	76.0	1	663	3 #4/0 XHHW
T250M	2 1/2"	142.0	1	1271	3 #300MCM XHHW
T300M	3"	173.0	1	1547	3 #350MCM XHHW
T350M	3 1/2"	292.0	1	2542	3 #350MCM XHHW
T400M	4"	324.0	1	2542	3 #350MCM XHHW