

# Thin wall conduit fittings (for EMT conduit)

Compression type fittings – zinc die cast

## COMPRESSION TYPE FITTINGS – ZINC DIE CAST

### Features:

- The split compression ring assures solid attachment to the conduit and good ground continuity
- The hex surfaces on the compression nut provide for easy wrenching to quickly and easily tighten the nut
- Concrete tight
- Threadless

### Standard material:

- Zinc

### Standard finish:

- Natural

### Straight connectors – insulated

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
1650DC	1/2"	50	8
1651DC	3/4"	25	11
1652DC	1"	15	17
1653DC	1 1/4"	10	31
1654DC	1 1/2"	10	39
1655DC	2"	5	56
1656DC	2 1/2"	12	93
1657DC	3"	12	120
1658DC	3 1/2"	6	149
1659DC	4"	6	172

## Straight connectors – non-insulated

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
650DC	1/2"	50	8
651DC	3/4"	25	11
652DC	1"	15	17
653DC	1 1/4"	10	31
654DC	1 1/2"	10	39
655DC	2"	5	56
656DC	2 1/2"	12	93
657DC	3"	12	120
658DC	3 1/2"	6	149
659DC	4"	6	172

## Couplings

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
660DC	1/2"	50	11
661DC	3/4"	25	16
662DC	1"	15	22
663DC	1 1/4"	10	40
664DC	1 1/2"	10	48
665DC	2"	5	64
666DC	2 1/2"	12	124
667DC	3"	12	144
668DC	3 1/2"	6	190
669DC	4"	6	228