

Thin wall conduit fittings (for EMT conduit)

Set screw type fittings – zinc die cast

SET SCREW TYPE FITTINGS – ZINC DIE CAST

Features:

- Tri-head set screw may be installed using a slotted, Phillips or Robertson head screwdriver
- Concrete tight when taped
- Threadless

Standard material:

- Zinc

Standard finish:

- Natural

Straight connectors – insulated

UL File No. E-22132



1450DC

1455DC



Cat. #	Size	Unit qty.	Wt. lbs. per 100
1450DC	1/2"	50	5
1451DC	3/4"	25	8
1452DC	1"	25	11
1453DC ^A	1 1/4"	10	20
1454DC ^A	1 1/2"	10	25
1455DC ^A	2"	5	37
1456DC ^{A C}	2 1/2"	12	59
1457DC ^{A C}	3"	12	78
1458DC ^{A C}	3 1/2"	6	101
1459DC ^{A C}	4"	6	120

^A Two tightening screws.

^C UL E-19189 and cUL Listed for EMT, IMC and rigid conduit.

Straight connectors – non-insulated

UL File No. E-22132



1450DC

1455DC



Cat. #	Size	Unit qty.	Wt. lbs. per 100
450DC	1/2"	50	5
451DC	3/4"	25	7
452DC	1"	25	11
453DC ^A	1 1/4"	10	21
454DC ^A	1 1/2"	10	25
455DC ^A	2"	5	36
456DC ^{A B}	2 1/2"	12	58
457DC ^{A B}	3"	12	77
458DC ^{A B}	3 1/2"	6	98
459DC ^{A B}	4"	6	117

^A Two tightening screws.

^B UL and cUL Listed for EMT, IMC and rigid conduit.

Couplings

UL File No. E-22132



1450DC

1455DC



Cat. #	Size	Unit qty.	Wt. lbs. per 100
460DC	1/2"	50	5
461DC	3/4"	25	7
462DC	1"	20	13
463DC ^B	1 1/4"	10	18
464DC ^B	1 1/2"	10	28
465DC ^B	2"	5	36
466DC ^{B C}	2 1/2"	12	64
467DC ^{B C}	3"	12	81
468DC ^{B C}	3 1/2"	6	98
469DC ^{B C}	4"	6	116

^B Four tightening screws.

^C UL and cUL Listed for EMT, IMC and rigid conduit.

Offset connectors – non-insulated

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
2400	1/2"	10	11
2401	3/4"	10	18
2402	1"	10	25