

# Flexible metallic conduit fittings

## Squeeze type – malleable iron

### SQUEEZE TYPE – MALLEABLE IRON

#### Applications:

- Used to squeeze and secure AC/MC cable to a box or enclosure

#### Features:

- High strength malleable iron
- 105°C temperature rating
- Used with armored cable and flexible metal conduit
- Male threads – NPSM

#### Standard materials:

- Malleable iron
- Steel locknut

#### Standard finish:

- Zinc plated

### Squeeze type<sup>®</sup> – straight – non-insulated

UL File No. E-19189



### Squeeze type<sup>®</sup> – straight – insulated

UL File No. E-19189



Cat. #	Trade size	Dia. of opening for cable	Dia. of bushed hole	Unit qty.	Wt. lbs. per 100
1707 <sup>2 6</sup>	3/8"	5/8"	3/8"	100	8
1708 <sup>2 7</sup>	1/2"	15/16"	5/8"	50	14
1709	3/4"	1 1/8"	3/4"	20	17
1710	1"	1 3/8"	1"	20	26
1711	1 1/4"	1 21/32"	1 5/16"	10	42
1712	1 1/2"	1 7/8"	1 1/2"	5	77
1713	2"	2 1/2"	2"	2	100
1714	2 1/2"	2 7/8"	2 3/8"	2	160
1715	3"	3 9/16"	3"	1	221
1721	3 1/2"	4"	3 13/32"	1	470
1722	4"	4 13/32"	3 31/32"	1	610

<sup>2</sup> UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP<sup>™</sup>).

MCAP<sup>™</sup> is a registered trademark of Southwire Company.

<sup>5</sup> UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b).

<sup>6</sup> Suitable for use with armored cable.

<sup>7</sup> Suitable for use with metal-clad cable.

FMC fittings

Cat. #	Trade size	Dia. of opening for cable	Dia. of bushed hole	Unit qty.	Wt. lbs. per 100
707 <sup>2 6</sup>	3/8"	5/8"	3/8"	100	7
708 <sup>2 7</sup>	1/2"	15/16"	5/8"	50	14
709	3/4"	1 1/8"	3/4"	20	22
710	1"	1 3/8"	1"	20	31
711	1 1/4"	1 21/32"	1 5/16"	10	46
712	1 1/2"	1 7/8"	1 1/2"	5	79
713	2"	2 1/2"	2"	2	101
714	2 1/2"	2 7/8"	2 3/8"	2	161
715	3"	3 9/16"	3"	1	220
721	3 1/2"	4"	3 13/32"	1	470
722	4"	4 13/32"	3 31/32"	1	610

<sup>2</sup> UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP<sup>™</sup>).

MCAP<sup>™</sup> is a registered trademark of Southwire Company.

<sup>5</sup> UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b).

<sup>6</sup> Suitable for use with armored cable.

<sup>7</sup> Suitable for use with metal-clad cable.