

# Rigid/intermediate grade conduit fittings

Set screw type fittings – malleable, steel, zinc die cast

Rigid fittings

## SET SCREW TYPE FITTINGS – MALLEABLE, STEEL, ZINC DIE CAST

### Standard materials:

- Malleable – 1/2" - 2", 5", 6"
- Steel – 2 1/2" - 4"
- Zinc die cast – 2 1/2" - 4"

### Straight connectors – insulated

UL File No. E-19189



150S



1456



Cat. # Malleable/steel	Cat. # zinc die cast	Size	Unit qty.	Wt. lbs. per 100
150S		1/2"	50	16
151		3/4"	25	27
152		1"	5	40
153		1 1/4"	10	50
154		1 1/2"	5	76
155 <sup>A</sup>		2"	2	110
1456 <sup>A</sup>	1456DC <sup>A</sup>	2 1/2"	2	210 <sup>F</sup>
1457 <sup>A</sup>	1457DC <sup>A</sup>	3"	1	282 <sup>F</sup>
1458 <sup>A</sup>	1458DC <sup>A</sup>	3 1/2"	1	380 <sup>F</sup>
1459 <sup>A</sup>	1459DC <sup>A</sup>	4"	1	400 <sup>F</sup>

<sup>A</sup> Two tightening screws.

<sup>F</sup> Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 1456-1459 and 1456DC-1459DC are UL and cUL Listed for EMT, rigid and IMC conduit.

### Straight connectors – non-insulated

UL File No. E-19189



150P



456



Cat. # Malleable/Steel	Cat. # Zinc Die Cast	Size	Unit qty.	Wt. lbs. per 100
150P		1/2"	50	16
151P		3/4"	25	26
152P		1"	5	40
153P		1 1/4"	10	50
154P		1 1/2"	5	76
155P		2"	2	110
456 <sup>A</sup>	456DC <sup>A</sup>	2 1/2"	2	210 <sup>F</sup>
457 <sup>A</sup>	457DC <sup>A</sup>	3"	1	281 <sup>F</sup>
458 <sup>A</sup>	458DC <sup>A</sup>	3 1/2"	1	380 <sup>F</sup>
459 <sup>A</sup>	459DC <sup>A</sup>	4"	1	400 <sup>F</sup>
160P <sup>A</sup>		5"	1	850
161P <sup>A</sup>		6"	1	1100

<sup>A</sup> Two tightening screws.

<sup>F</sup> Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 456-459 and 456DC-459DC are UL and cUL Listed for EMT, rigid and IMC conduit.

## Couplings

UL File No. E-19189



160



466



Cat. # Malleable/Steel	Cat. # Zinc Die Cast	Size	Unit qty.	Wt. lbs. per 100
160		1/2"	25	27
161		3/4"	20	40
162		1"	5	52
163		1 1/4"	10	70
164		1 1/2"	5	104
165 <sup>B</sup>		2"	2	160
466 <sup>B</sup>	466DC <sup>B</sup>	2 1/2"	2	300 <sup>F</sup>
467 <sup>B</sup>	467DC <sup>B</sup>	3"	1	400 <sup>F</sup>
468 <sup>B</sup>	468DC <sup>B</sup>	3 1/2"	1	500 <sup>F</sup>
469 <sup>B</sup>	469DC <sup>B</sup>	4"	1	600 <sup>F</sup>
170C <sup>B</sup>		5"	1	1500
171C <sup>B</sup>		6"	1	1800

<sup>B</sup> Four tightening screws.

<sup>F</sup> Wt. lbs. per 100 for malleable only. See EMT section for applicable steel EMT information. 466-469 and 466DC-469DC are UL and cUL Listed for EMT, rigid and IMC conduit.