

# Rigid/intermediate grade conduit fittings

## Conduit couplings

### RIGID CONDUIT COUPLINGS – STEEL

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Standard material:

- Galvanized steel

UL File No. E-25501



Cat. #	Size	Unit qty.	Wt. lbs. per 100
RC50	1/2"	10	12
RC75	3/4"	10	18
RC100	1"	10	29
RC125	1 1/4"	5	38
RC150	1 1/2"	5	52
RC200	2"	5	69
RC250	2 1/2"	2	181
RC300	3"	1	220
RC350	3 1/2"	1	377
RC400	4"	1	298
RC500	5"	1	477
RC600	6"	1	684

### RIGID CONDUIT COUPLINGS – ALUMINUM

#### Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

#### Features:

- Lightweight
- Easy to install
- Corrosion-resistant

#### Standard material:

- Aluminum

UL File No. E-324286



Cat. #	Size	Unit qty.	Wt. lbs. per 100
RC50SA	1/2"	50	6
RC75SA	3/4"	50	9
RC100SA	1"	50	13
RC125SA	1 1/4"	50	19
RC150SA	1 1/2"	50	23
RC200SA	2"	20	35
RC250SA	2 1/2"	12	68
RC300SA	3"	12	91
RC350SA	3 1/2"	12	108
RC400SA	4"	12	142
RC500SA	5"	1	242
RC600SA	6"	1	320