


EMT Strut Clamps



Features

- For use with EMT conduit

Standard Material

- Steel

Standard Finish


- Zinc plated

Application

- Use to support EMT conduit from strut channel

Catalog Number	Size	Conduit Size (mm)	Material Thickness	Hole Diameter	A	B	C	D	Bolt Size
(inch)									
USC-E050	½"	17.93	0.060 (±0.005)	0.28	0.690	0.706	0.6340±0.015	0.325	¼"-20*1"
USC-E075	¾"	23.42				0.922	0.7420±0.015		
USC-E100	1"	29.54				1.163	0.8625±0.015		
USC-E125	1-¼"	38.35				1.510	0.0360±0.015		
USC-E150	1-½"	44.20	0.060 (±0.005)	0.34	0.820	1.740	0.1510±0.015	0.400	5/16-18*1-¼"
USC-E200	2"	60.33				2.375	1.4685±0.015		
USC-E250	2-½"	73.03				2.875	1.7185±0.015		
USC-E300	3"	88.90				3.500	2.0310±0.015		
USC-E350	3-½"	101.60	0.118 (±0.005)	0.42	0.875	4.000	2.2810±0.015	0.480	3/8-16*1-¼"
USC-E400	4"	114.30				4.500	2.5310±0.015		
USC-E500	5"	141.30				5.563	3.0625±0.015		
USC-E600	6"	168.30				6.625	3.5935±0.015		

Rigid Strut Clamps



Features

- For use with IMC/Rigid conduit

Standard Material

- Steel

Standard Finish

- Zinc plated

Application

- Use to support IMC/Rigid conduit from strut channel

Catalog Number	Size	Conduit Size (mm)	Material Thickness	Hole Diameter	A	B	C	D	Bolt Size
(inch)									
USC-R050	½"	21.34	0.0641 (±0.005)	0.28	0.690	0.840	0.7010±0.015	0.325	¼"-20*1"
USC-R075	¾"	26.67				1.050	0.8060±0.015		
USC-R100	1"	33.40				1.315	0.9385±0.015		
USC-R125	1-¼"	42.16				1.660	1.1110±0.015		
USC-R150	1-½"	48.26	0.1034 (±0.005)	0.34	0.820	1.900	1.2310±0.015	0.400	5/16-18*1-¼"
USC-R200	2"	60.33				2.375	1.4685±0.015		
USC-R150	2-½"	73.03				2.875	1.7185±0.015		
USC-R300	3"	88.90				3.500	2.0310±0.015		
USC-R350	3-½"	101.60	0.118 (±0.005)	0.42	0.875	4.000	2.2810±0.015	0.480	3/8-16*1-¼"
USC-R400	4"	114.30				4.500	2.5310±0.015		
USC-R500	5"	141.30				5.563	3.0625±0.015		
USC-R600	6"	168.30				6.625	3.5935±0.015		