

TECHNICAL DATA SHEET LOW VOLTAGE POWER CABLE

Cable Description:


Cu / PVC / PVC 1kV 3X10 mm² black 90 °C (Flex)
IEC 60502-1 FR-IEC 60332-1

Design and Construction Data:		
Reference Manufacturing Standards		IEC/BS EN 60228, IEC 60502-1
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	160 °C
Rated Voltage ' U ₀ / U '	kV	0.6 / 1.0
Number of Conductors x Cross-Section	mm²	3 x 10
Conductor Material & Shape		Copper & Flexible Class 5 non-compacted Round Shape
Insulation Material		PVC
Conductor Nominal Insulation Thickness	mm	1.00
Insulation Color		RED, YELLOW, BLUE
Outer Sheath Material		PVC
Colour of Outer Sheath		BLACK
Approximate Cable Overall Diameter	mm	17.4
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	1.9100
Max Conductor AC resistance @ 90 °C	ohms/km	2.4355
Max Conductor Short Circuit Current @ 1 Second	kA	1.00
Current Carry Capacity		
Laid in air @ 40 °C Ambient Temperature		
Free In Air	A	67
In Pipes	A	52
Laid in Ground		
Direct Laid	A	76
Laid In Duct	A	62
Laid in Ground with the following conditions: Ambient Ground Temperature: 35 °C Depth of laying in ground: 0.5 m Soil Thermal Resistivity: 1.2 °K.m/W		
Additional Data:		
Maximum pulling Tension	kN	1.50
Maximum side wall pressure	kN/m	10.8
Minimum Bending Radius	mm	139
The Cable shall meet all Test requirements of: IEC/BS EN 60228, IEC 60502-1, IEC 60332-1		
Packing Data:		
Drum Type		Non-Returnable
Length of Cable per drum (± 5%)	m	1000
Drum Dimensions "Height x Width" (Approx.)	m	1.1 x 0.81
Gross Weight (Approximate without Lagging)	kg	592

TECHNICAL DATA SHEET **LOW VOLTAGE POWER CABLE**

Cable Marking:

BAHRA CABLES CO. KSA 3 X 10 mm² Cu / PVC / PVC (Flex) 600 / 1000 V IEC 60502-1 FR IEC 60332-1
Manufacturing Year - Meter marked

Cable Drawing


Description	Cu / PVC / PVC 1kV 3X10 mm ² black 90 °C (Flex)	Approx. Diameter
1	Core	
	Flexible Copper Conductor	3.99
	PVC insulated	5.99
2	PVC Compound	14.04
3	PVC Outer Sheathing	17.42