


## TECHNICAL DATA SHEET LOW VOLTAGE BUILDING WIRE

Cable Description:

Cu /LS0H-XL 450 / 750 V H07Z-R 1.5 mm<sup>2</sup> RM BLACK

Design and Construction Data:		
Reference Manufacturing Standards		IEC 60228, BS EN 50525-3-41
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	250
Rated Voltage	V	450 / 750
Conductor Size	mm <sup>2</sup>	1.5
Conductor Material & Shape		Copper & Stranded Class 2 non-compacted Round Shape
Insulation Material		LS0H-XL
Nominal Insulation Thickness	mm	0.70
Insulation Color		BLACK
Approximate Wire Overall Diameter	mm	3
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	12.1000
Max Conductor AC resistance @ 90 °C (Two/Three) Conductors	ohms/km	15.4287 / 15.4287
Max Conductor Short Circuit Current @ 1 Second	KA	0.21
Current Carry Capacity @ 30 °C Ambient Temperature		
Enclosed in conduit <sup>(1)</sup>		
Two Insulated Conductors Single Phase ac or dc	A	23
Three or Four Insulated Conductors Three Phase ac	A	20
Clipped direct <sup>(2)</sup>		
Two Insulated Conductors Single Phase ac or dc	A	25
Three or Four Insulated Conductors Three Phase ac	A	23
(1) Current carrying capacity based on IEE wiring regulation method B cables single ac or dc / three phase ac, enclosed in conduit on a wall or in trunking etc. at 30 °C ambient temperature". (2) Current carrying capacity based on IEE wiring regulation method C cables single ac or dc / three phase , clipped direct at 30 °C ambient temperature". * ref (IEE Wiring Regulations 17th edition Table 4E1A)		
The Cable shall meet all Test requirements of: IEC/BS EN 60228, BS EN 50525-3-41, Formally BS 7211:1998 which is superseded, IEC 60332-1, IEC 60754-1, IEC 61034		
Packing Data:		
Type		Coil
Length of Cable per Coil (± 2%)	m	92
Gross Weight (Approximate)	kg	2
Cable Marking:		
BAHRA CABLES CO. KSA 1.5 MM <sup>2</sup> CU/LS0H-XL 90 DEG C 450/750 V H07Z-R BS EN 50525-3-41 BASEC		
Cable Drawing		
		
Description	Cu /LS0H-XL 450 / 750 V H07Z-R 1.5 mm <sup>2</sup> RM BLACK	Approx. Diameter
1	Copper conductor with round shape	1.52
2	LS0H-XL Insulation	2.92