


**TECHNICAL DATA SHEET
LOW VOLTAGE THHN BUILDING WIRE**

Cable Description:

6 AWG CU / PVC (THHN)

Design and Construction Data:		
Reference Manufacturing Standards		American Designation
Max. Permissible Continuous Conductor Temp	°C	105
Max. Conductor Short Circuit Temp for 5 Seconds	°C	150
Rated Voltage	V	600
Conductor Size	AWG	6
Number of wires per conductor		19
Wires Combination		Round Wires Unilay-Stranded
Insulation Material		Polyvinyl Chloride (PVC)
Nominal Insulation Thickness	mm	0.76
Insulation Color		WHITE
Outer Nylon Jacket		Polyamide Nylon
Approximate Wire Overall Diameter	mm	6.3
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	1.3500
Max Conductor AC resistance @ 105 °C	ohms/km	1.8012
Max Conductor Short Circuit Current @ 1 Second	kA	1.0604
Current Carry Capacity @ 30 °C Ambient Temperature ⁽¹⁾		
Single-Insulated Conductor		
Laid in free air	A	105
Not more than Three Current-Carrying Conductors ⁽²⁾		
Laid in Race way, Cable, or Earth {Directly Buried}	A	75
(i) - Ampacity based on NEC Table 310.15(B)(16) (Formerly Table 310.16) & Table 310.15(B)(17) (Formerly Table 310.17) - Refer to 310.15(B)(2)(a) for the ampacity correction factors where the ambient temperature is other than 30°C. - Refer to 110.14(C) for temperature rating limitations. - See Section 240.4 (D) for conductor overcurrent protection limitations. (ii) Refer to 310.15(B)(3)(a) for more than three current-carrying conductors		
The wire is generally according to: THHN designation		
Packing Data:		
Type		Spool
Length of Cable per Spool (± 2%)	m	152
Gross Weight (Approximate)	kg	22
Cable Marking:		
BAHRA CABLES CO. KSA THHN / THWN 6 AWG 600 Volts VW-1 GASOLINE & OIL RESISTANT II 105 °C 'Meter marked'		
Cable Drawing		
		
Description	6 AWG CU / PVC (THHN)	Approx. Diameter
1	Copper conductor with round shape	4.51
2	PVC Insulation	6.03
3	Polyamide Nylon Jacketing	6.29