


Product datasheet

Specifications



Front plate, PrismaSeT P and G,
for NSX/CVS250 3P/4P, 5M,
vertical, fixed, toggle/Rotary
handle, white, RAL 9003

LVS03243

Main

Range	PrismaSeT
Range Of Produc	PrismaSeT G PrismaSeT P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type Of Front Plate	Cut-out
Installed Device	ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS250 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Poles Description	4 x 3P: mounting plate support: CVS100...160 vertical installation 3 x 4P: mounting plate support: CVS100...160 vertical installation 4 x 3P: mounting plate support: CVS250 vertical installation 3 x 4P: mounting plate support: CVS250 vertical installation 4 x 3P: mounting plate support: NSX100...160 vertical installation 3 x 4P: mounting plate support: NSX100...160 vertical installation 4 x 3P: mounting plate support: NSX250 vertical installation 3 x 4P: mounting plate support: NSX250 vertical installation 2 x 3P: mounting plate support: NSX100...160 vertical installation 2 x 4P: mounting plate support: NSX100...160 vertical installation 2 x 3P: mounting plate support: NSX250 vertical installation 2 x 4P: mounting plate support: NSX250 vertical installation
Operating Position	Vertical

Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Connection Position	Linery FC Direct connection
Number Of Vertical Modules [50 Mm]	5
Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ASTA
Material	Steel
Surface Finish	Matt Textured
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	250 mm
Width	500 mm
Net Weight	0.82 kg
Quantity Per Set	Set of 1

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 3P 4 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 4P 3 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 3P 4 Linergy FC 8
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 3P 4 Linergy FC 8
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 4P 3 Linergy FC 8
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 4P 3 Linergy FC 8
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 3P 4 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 4P 3 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 3P 4 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 4P 3 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 3P 4 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 4P 3 direct 10
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout toggle vertical 3P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout toggle vertical 4P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout direct front rotary handle vertical 3P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout direct front rotary handle vertical 4P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout motor mechanism vertical 3P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout motor mechanism vertical 4P 2 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 Linergy FC 7
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 Linergy FC 7
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 Linergy FC 7
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 Linergy FC 7
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 direct 9
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 3P 4 Linergy FC 8
650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 4P 3 Linergy FC 8
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed toggle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed toggle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed toggle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed toggle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed toggle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed toggle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed toggle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed toggle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	26.0 cm
Package 1 Length	51.0 cm
Package 1 Weight	834.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	16.5 cm
Package 2 Width	27.4 cm
Package 2 Length	52.7 cm
Package 2 Weight	8.537 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	270
Package 3 Height	94.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	242.0 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH


Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
✓	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Dimensions



- All dimensions are approximate and are in mm.
- Also see technical documentation.